



Project / Job Name: \_\_\_\_\_

Location: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Notes: \_\_\_\_\_

**S9403** - 7 Watt PAR20 LED; 4000K; 25 deg. Beam Angle; Medium base; 120 Volt



**GENERAL**

Company	SATCO
EA Height	3.55
EA Width	2.56
EA Length	2.56
Center Beam Candle Power	1100
Dimmable Text	Forward Phase or Reverse Phase
Lamp Filament	LED
Fixture Type	PAR
Status	Obsolete
CCT Selectable	No
Wattage Selectable	No
Finish Family	No Finish
Amps	0.058A
Has Camera	No
IOT Enabled	No
Lens Finish	Clear
Lensed	Yes
Operating Position	Universal
Power Factor	0.9
SDS Class	LED_Lamp
Indoor Outdoor	Indoor, Outdoor
Product Technology	LED
Incandescent Equivalent	50W

**ELECTRICAL**

CCT (Kelvin Temp)	4000K
Dimmable	Yes-Dimmable
Hours Rated	25000
Beam Angle (degree)	25
Color Temp	Cool White
CRI	80+
Dimming Type	120V only, Phase cut
Operating Temp	-20C (-4F) to +45C (+113F)
Lumens	525L
Volts	120v
Watts	7W

**PHYSICAL**

Lamp Base	Medium
Finish	Clear
Housing Color	Silver
ANSI Base	E26
Lamp Type	PAR20
MOD Lamps	2.5
MOL	3.03

**ADDITIONAL INFO**

Warranty	5-Years
Rated For Enclosed Fixture	Yes

**PACKAGING**

UPC	045923094033
Case Cube	0.5382
Case Height	8.87
Case Length	11.82
Case Quantity	24
Case UPC	10045923094030
Case Weight	5.62
Case Width	8.87
EA Cube	0.0135
EA Height	3.55
EA Length	2.56
EA Quantity	1
EA Weight	0.13
EA Width	2.56
Inner Cube	0.1041
Inner Height	3.94
Inner Length	8.27
Inner Quantity	6
Inner UPC	20045923094037
Inner Weight	1.02
Inner Width	5.52
Pack Type	Box
Web Length	3.03
Web Width	2.5

**COMPLIANCE**

CA T20 Compliant Substitute	S8494
FCC Compliant	Yes
IP Rating	IP65
Location Rating	Wet
ROHS Compliant	Yes
Safety Listing	cULus - Certified, cULus - Listed
California Ban	Non-Compliant
DLC Approved	No
Title 20	No
T24 Compliant	No
US State Ban	CA