



62-1770 - Blink Pro Plus; 24 Watt; 5.5 in. x 24 in.; Surface Mount LED; CCT Selectable; 90 CRI; White Finish; 120/277 Volt; Rectangular Shape


GENERAL

Company	NUVO
EA Height	5.91
EA Width	1.18
EA Length	24.41
Bulb Included	Integrated
Dimmable Text	Forward Phase or Reverse Phase; 120V only
Material	Die-cast Aluminum
Fixture Type	Surface Mount
Status	Active
Style	Contemporary
Surge Protection	Built-in surge protection - 2.5KV
Total Harmonic Distortion	<20%
CCT Selectable	Yes
Wattage Selectable	No
Finish Family	White
Additional Info	UGR - 23.4; Hi pot - DC-1550V; Edge-lit - Yes
Amps	0.200/0.087A
Has Camera	No
IOT Enabled	No
Lens Finish	Frost
Lens Material	Poly methyl methacrylate (PMMA)
Power Factor	0.9
SDS Class	LED_Fixture
Indoor Outdoor	Indoor
Product Technology	LED
Incandescent Equivalent	125W

ELECTRICAL

CCT (Kelvin Temp)	2700K/3000K/3500K/4000K/5000K
Dimmable	Yes-Dimmable
Hours Rated	50000
Beam Angle (degree)	110
Color Temp	Warm White to Natural Light
CRI	90+
Dimming Type	120V only, Phase cut
Operating Frequency	60Hz
Operating Temp	-20C (-4F) to +40C (+104F)
Lumens	1650L-1870L
Volts	120V/277V
Watts	24W

PHYSICAL

Lamp Base	Integrated
Finish	WHITE
ANSI Base	Integrated
Lamp Type	Integrated LED
Fixture Shape	Rectangle

ADDITIONAL INFO

Warranty	5-Years
Installation Notes	Compatible with 3" & 4" J-box and pancake J-box

FEATURES

Flicker Free	No
--------------	----

PACKAGING

UPC	045923612992
Case Cube	0.8004
Case Height	6.69
Case Length	25.0
Case Quantity	6
Case UPC	10045923612999
Case Weight	29.38
Case Width	8.27
EA Cube	0.0985
EA Height	5.91
EA Length	24.41
EA Quantity	1
EA Weight	4.72
EA Width	1.18
Inner Cube	0.0
Inner Height	0.0
Inner Length	0.0
Inner Quantity	0
Inner Weight	0.0
Inner Width	0.0
Pack Type	Box
Web Height	1.06
Web Length	23.98
Web Width	5.61

COMPLIANCE

CA Prop 65	Lead
FCC Compliant	Yes
Location Rating	Damp
ROHS Compliant	Yes
Safety Listing	cETLus - Listed
California Ban	California T24 Listed
DLC Approved	No
Energy Star Certified	No
Title 20	Exempt
T24 Compliant	Yes