



Project / Job Name: \_\_\_\_\_

Location: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Notes: \_\_\_\_\_

**62-1778** - Blink Pro Plus; 34 Watt; 19 in.; Surface Mount LED; CCT Selectable; 90 CRI; White Finish; 120/277 Volt; Round Shape



**GENERAL**

Company	NUVO
EA Height	19.29
EA Width	1.18
EA Length	19.29
Bulb Included	Integrated
Diameter	19.0
Dimmable Text	Forward Phase or Reverse Phase; 120V only
Material	Die-cast Aluminum
Fixture Type	Surface Mount
Status	Active
Style	Contemporary
Surge Protection	Built-in surge protection - 2.5KV
Total Harmonic Distortion	<20%
CCT Selectable	Yes
Wattage Selectable	No
Finish Family	White
Additional Info	UGR - 21.9; Hi pot - DC-1550V; Edge-lit - Yes
Amps	0.283/0.123A
Has Camera	No
IOT Enabled	No
Lens Finish	Frost
Lens Material	Poly methyl methacrylate (PMMA)
Power Factor	0.9
SDS Class	LED_Fixture
Indoor Outdoor	Indoor
Product Technology	LED
Incandescent Equivalent	125W

**PACKAGING**

UPC	045923613074
Case Cube	1.9856
Case Height	20.87
Case Length	19.88
Case Quantity	6
Case UPC	10045923613071
Case Weight	39.37
Case Width	8.27
EA Cube	0.2541
EA Height	19.29
EA Length	19.29
EA Quantity	1
EA Weight	6.27
EA Width	1.18
Pack Type	Box
Web Height	1.06
Web Width	19.0

**COMPLIANCE**

CA Prop 65	Lead
FCC Compliant	Yes
Location Rating	Damp
ROHS Compliant	Yes
Safety Listing	cETLus - Listed
California Ban	California T24 Listed
DLC Approved	No
Energy Star Certified	No
Title 20	Exempt
T24 Compliant	Yes

**ELECTRICAL**

CCT (Kelvin Temp)	2700K/3000K/3500K/4000K/5000K
Dimmable	Yes-Dimmable
Hours Rated	50000
Beam Angle (degree)	110
Color Temp	Warm White to Natural Light
CRI	90+
Dimming Type	120V only, Phase cut
Operating Frequency	60Hz
Operating Temp	-20C (-4F) to +40C (+104F)
Lumens	2600L-2740L
Volts	120V/277V
Watts	34W

**PHYSICAL**

Lamp Base	Integrated
Finish	WHITE
ANSI Base	Integrated
Lamp Type	Integrated LED
Fixture Shape	Round

**ADDITIONAL INFO**

Warranty	5-Years
Installation Notes	Compatible with 3" & 4" J-box and pancake J-box

**FEATURES**

Flicker Free	No
--------------	----