



Project / Job Name: \_\_\_\_\_

Location: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Notes: \_\_\_\_\_

**62-2035 - Barnett; 21 Inch LED Flush Mount; Matte Black; Silk Screened Acrylic Lens**



**GENERAL**

|                           |                                   |
|---------------------------|-----------------------------------|
| Company                   | NUVO                              |
| EA Height                 | 10.63                             |
| EA Width                  | 23.62                             |
| EA Length                 | 23.62                             |
| Mounting Height           | 1.63                              |
| Bulb Included             | Integrated                        |
| Diameter                  | 20.88                             |
| Dimmable Text             | Forward Phase                     |
| Material                  | Steel                             |
| Fixture Type              | Flush Mount                       |
| Status                    | Active                            |
| Style                     | Modern                            |
| Surge Protection          | Built-in surge protection - 2.5KV |
| Total Harmonic Distortion | <15%                              |
| CCT Selectable            | No                                |
| Wattage Selectable        | No                                |
| Collection                | Barnett                           |
| Finish Family             | Black                             |
| Amps                      | 0.200A                            |
| Mounting Diameter         | 9.88                              |
| Has Camera                | No                                |
| IOT Enabled               | No                                |
| Lens Finish               | Silk Screened                     |
| Lens Material             | Acrylic                           |
| Power Factor              | 0.9                               |
| SDS Class                 | LED Fixture                       |
| Shade Shape               | Ribbon                            |
| Sloped Ceiling Compatible | Yes                               |
| Indoor Outdoor            | Indoor                            |
| Product Technology        | LED                               |
| Incandescent Equivalent   | 120W                              |

**PACKAGING**

|               |                |
|---------------|----------------|
| UPC           | 045923620737   |
| Case Cube     | 3.432          |
| Case Height   | 10.63          |
| Case Length   | 23.62          |
| Case Quantity | 1              |
| Case UPC      | 10045923620734 |
| Case Weight   | 11.02          |
| Case Width    | 23.62          |
| EA Cube       | 3.432          |
| EA Height     | 10.63          |
| EA Length     | 23.62          |
| EA Quantity   | 1              |
| EA Weight     | 11.02          |
| EA Width      | 23.62          |
| Pack Type     | Color Box      |
| Web Height    | 7.63           |
| Web Width     | 20.88          |

**COMPLIANCE**

|                 |                 |
|-----------------|-----------------|
| ADA Compliant   | No              |
| Air Tight       | No              |
| CA Prop 65      | Lead            |
| FCC Compliant   | Yes             |
| Location Rating | Dry             |
| ROHS Compliant  | Yes             |
| Safety Listing  | cETLus - Listed |
| California Ban  | Lawful for sale |
| Title 20        | Exempt          |
| T24 Compliant   | No              |

**ELECTRICAL**

|                     |                            |
|---------------------|----------------------------|
| CCT (Kelvin Temp)   | 3000K                      |
| Dimmable            | Yes-Dimmable               |
| Hours Rated         | 30000                      |
| Beam Angle (degree) | 120                        |
| Color Temp          | Soft White                 |
| CRI                 | 90+                        |
| Dimming Type        | 120V only, Phase cut       |
| Operating Frequency | 60Hz                       |
| Operating Temp      | -20C (-4F) to +40C (+104F) |
| Lumens              | 1920L                      |
| Volts               | 120v                       |
| Watts               | 24W                        |

**PHYSICAL**

|               |                |
|---------------|----------------|
| Lamp Base     | Integrated     |
| Finish        | Matte Black    |
| ANSI Base     | Integrated     |
| Lamp Type     | Integrated LED |
| Fixture Shape | Round          |

**ADDITIONAL INFO**

|          |         |
|----------|---------|
| Warranty | 3-Years |
|----------|---------|