



Project / Job Name: \_\_\_\_\_

Location: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Notes: \_\_\_\_\_

**65-1181 - Momentum; 4 Foot LED Connectable Linear Strip; Up and Down Selectable; White Finish**



**GENERAL**

Company	NUVO
EA Height	3.66
EA Width	4.72
EA Length	48.19
Bulb Included	Integrated
Material	Aluminum
Fixture Type	Linear
Product Notes	Max Wattage when connected at 120V: 700W; Max Wattage when connected at 277V: 1400W; Max Wattage when connected at 347V: 1750W
Status	Active
Surge Protection	Built-in surge protection - 2KV
Total Harmonic Distortion	11.3%
CCT Selectable	Yes
Wattage Selectable	Yes
Finish Family	White
Amps	0.250-0.086/0.333-0.115/0.417-0.144A
Has Camera	No
IOT Enabled	No
Lens Finish	White
Lens Material	Polycarbonate (PC)
Lensed	Yes
Power Factor	0.93
Sloped Ceiling Compatible	When suspended
Indoor Outdoor	Indoor
Product Technology	LED
Incandescent Equivalent	175W-250W

**PACKAGING**

UPC	045923654244
Case Cube	2.3539
Case Height	8.11
Case Length	48.98
Case Quantity	4
Case UPC	10045923654241
Case Weight	28.56
Case Width	10.24
EA Cube	0.4818
EA Height	3.66
EA Length	48.19
EA Quantity	1
EA Weight	7.14
EA Width	4.72
Pack Type	Box
Web Height	3.4
Web Length	46.5
Web Width	2.36

**COMPLIANCE**

CA Prop 65	Lead
DLC ID	S-RJQBWB
FCC Compliant	Yes
Location Rating	Damp
ROHS Compliant	Yes
Safety Listing	cETLus
California Ban	Lawful for sale
DLC Approved	Yes
Title 20	Exempt
T24/JA8 Compliant	No

**ELECTRICAL**

CCT (Kelvin Temp)	3000K/4000K/5000K
Dimmable	Yes-Dimmable
Hours Rated	50000
Beam Angle (degree)	120
Color Temp	Soft White to Natural Light
CRI	80+
Dimming Type	0-10V Dimming
Operating Frequency	50/60Hz
Operating Temp	-4F to +113F (-20C to +45C)
Lumens	3300L/4400L/5500L
Volts	120V-347V
Watts	30W/40W/50W

**PHYSICAL**

Lamp Base	Integrated
Finish	WHITE
ANSI Base	Integrated
Lamp Type	Integrated LED
Fixture Shape	Linear

**ADDITIONAL INFO**

Warranty	5-Years
----------	---------

**FEATURES**

Flicker Free	Yes
--------------	-----