



Project / Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

65-1540 - LED Flood Light; 35/25/15 Wattage Selectable; 3K/4K/5K CCT Selectable; Beam Angle Selectable; Bronze Finish; 120-347 Volt



GENERAL

Company	NUVO
EA Height	11.89
EA Width	4.72
EA Length	10.63
Bulb Included	Integrated
Dimmable Text	0-10V Dimming
Material	Die-cast Aluminum
Fixture Type	Flood Light
Product Notes	Default Wattage: 35W
Status	Active
Style	Utility
Surge Protection	Built-in surge protection - 6KV
Total Harmonic Distortion	<20%
Wire Color	Black
CCT Selectable	Yes
Wattage Selectable	Yes
Finish Family	Bronze
Amps	0.290-0.100/0.210-0.070/0.130-0.040A
Lens Finish	Clear
Lens Material	Glass
Lensed	Yes
Starfish Operational Humidity	20% to 90% R.H.
Photo Cell	Has Photocell
Power Factor	>0.9
Indoor Outdoor	Outdoor
Product Technology	LED
Incandescent Equivalent	100W-175W

ELECTRICAL

CCT (Kelvin Temp)	3000K/4000K/5000K
Dimmable	Yes-Dimmable
Hours Rated	50000
Beam Angle (degree)	135x125/120x120/90x90
Color Temp	Soft White to Natural Light
CRI	80
Dimming Type	0-10V Dimming
Operating Frequency	50/60Hz
Operating Temp	-40C (-40F) to +50C (+122F)
HID Equivalent	125W-200W
Lumens	1998L-5292L
Volts	120V-347V
Watts	35W/25W/15W

PHYSICAL

Lamp Base	Integrated
Finish	BRONZE
ANSI Base	Integrated
Lamp Type	Integrated LED
Fixture Shape	Rectangle

ADDITIONAL INFO

Warranty	5-Years
----------	---------

PACKAGING

UPC	045923412585
Case Cube	2.3858
Case Height	12.68
Case Length	21.85
Case Quantity	6
Case UPC	10045923412582
Case Weight	27.92
Case Width	14.88
EA Cube	0.3452
EA Height	11.89
EA Length	10.63
EA Quantity	1
EA Weight	3.92
EA Width	4.72
Inner Cube	0.0
Pack Type	Box
Web Height	8.8
Web Length	7.8
Web Width	3.15

COMPLIANCE

Bug Rating	B4-U0-G5
CA Prop 65	Lead
DLC ID	S-M5DB5B
FCC Compliant	Yes
IP Rating	IP65
Location Rating	Wet
NSF Approved	No
ROHS Compliant	Yes
Safety Listing	cULus - Listed
California Ban	Lawful for sale
DLC Approved	Yes
Title 20	Exempt
T24 Compliant	No