



Project / Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

65-1542 - LED Flood Light; 150/125/100 Wattage Selectable; 3K/4K/5K CCT Selectable; Beam Angle Selectable; Bronze Finish; 120-347 Volt



GENERAL

Company	NUVO
EA Height	8.74
EA Width	14.76
EA Length	16.46
Bulb Included	Integrated
Dimmable Text	0-10V Dimming
Material	Die-cast Aluminum
Fixture Type	Flood Light
Product Notes	Default Wattage: 150W
Status	Active
Style	Utility
Surge Protection	Built-in surge protection - 6KV
Total Harmonic Distortion	<20%
Wire Color	Black
CCT Selectable	Yes
Wattage Selectable	Yes
Finish Family	Bronze
Amps	1.250-0.430/1.040-0.360/0.830-0.290A
Lens Finish	Clear
Lens Material	Glass
Lensed	Yes
Starfish Operational Humidity	20% to 90% R.H.
Photo Cell	Has Photocell
Power Factor	>0.9
Indoor Outdoor	Outdoor
Product Technology	LED
Incandescent Equivalent	350W-500W

ELECTRICAL

CCT (Kelvin Temp)	3000K/4000K/5000K
Dimmable	Yes-Dimmable
Hours Rated	50000
Beam Angle (degree)	135x125/120x120/90x90
Color Temp	Soft White to Natural Light
CRI	80
Dimming Type	0-10V Dimming
Operating Frequency	50/60Hz
Operating Temp	-40C (-40F) to +50C (+122F)
HID Equivalent	400W-600W
Lumens	15024L-22754L
Volts	120V-347V
Watts	150W/125W/100W

PHYSICAL

Lamp Base	Integrated
Finish	BRONZE
ANSI Base	Integrated
Lamp Type	Integrated LED
Fixture Shape	Rectangle

ADDITIONAL INFO

Warranty	5-Years
----------	---------

PACKAGING

UPC	045923412608
Case Cube	1.2288
Case Height	8.74
Case Length	16.46
Case Quantity	1
Case UPC	10045923412605
Case Weight	12.76
Case Width	14.76
EA Cube	1.2288
EA Height	8.74
EA Length	16.46
EA Quantity	1
EA Weight	12.76
EA Width	14.76
Inner Cube	0.0
Pack Type	Box
Web Height	14.22
Web Length	12.51
Web Width	5.57

COMPLIANCE

Bug Rating	B4-U0-G5
CA Prop 65	Lead
DLC ID	S-CYKVFG
FCC Compliant	Yes
IP Rating	IP65
Location Rating	Wet
NSF Approved	No
ROHS Compliant	Yes
Safety Listing	cULus - Listed
California Ban	Lawful for sale
DLC Approved	Yes
Title 20	Exempt
T24 Compliant	No