SATCO | NUVO



Project / Job Name:

Location:

Fixture Type:

Notes:

65-1543 - LED Flood Light; 300/250/200 Wattage Selectable; 3K/4K/5K CCT Selectable; Beam Angle Selectable; Bronze Finish; 120-347 Volt

GENERAL

Company	NUVO
EA Height	9.65
EA Width	17.72
EA Length	19.29
Bulb Included	Integrated
Material	Die-cast Aluminum
Fixture Type	Flood Light
Product Notes	Default Wattage: 300W
Status	Active
Style	Utility
Surge Protection	Built-in surge protection - 6KV
Total Harmonic Distortion	<20%
Wire Color	Black
CCT Selectable	Yes
Wattage Selectable	Yes
Finish Family	Bronze
Amps	2.500-0.860/2.080-0.720/1.670-0.580A
Integrated Features	Integrated Photocell
Lens Finish	Clear
Lens Material	Glass
Lensed	Yes
Starfish Operational Humidity	20% to 90% R.H.
Photo Cell	Has Photocell
Power Factor	>0.9
Indoor Outdoor	Outdoor
Product Technology	LED
Incandescent Equivalent	600W-800W
Serviceable Battery	No
Battery Indicator	No
Digital Display	No

ELECTRICAL

CCT (Kelvin Temp)	3000K/4000K/5000K
Dimmable	Yes-Dimmable
Hours Rated	50000
Beam Angle (degree)	135x125/110x110/95x95
Color Temp	Soft White to Natural Light
CRI	80+
Dimming Type	0-10V Dimming
Operating Frequency	50/60Hz
Operating Temp	-40F to +122F (-40C to +50C)
HID Equivalent	650W-1000W
Lumens	29611L-47273L
Volts	120V-347V
Watts	300W/250W/200W
Max Lumens	47273L

PHYSICAL

Lamp Base	Integrated
Finish	BRONZE
ANSI Base	Integrated
Lamp Type	Integrated LED
Fixture Shape	Rectangle

ADDITIONAL INFO

Warranty	5-Years

PACKAGING

UPC	045923412615
Case Cube	1.9089
Case Height	9.65
Case Length	19.29
Case Quantity	1
Case UPC	10045923412612
Case Weight	20.34
Case Width	17.72
EA Cube	1.9089
EA Height	9.65
EA Length	19.29
EA Quantity	1
EA Weight	20.34
EA Width	17.72
Pack Type	Box
Web Height	17.0
Web Length	16.35
Web Width	6.74

COMPLIANCE

Bug Rating	B4-U0-G5
CA Prop 65	Lead
DLC ID	S-2Z9ZF6
FCC Compliant	Yes
IP Rating	IP65
Location Rating	Wet
NSF Approved	No
ROHS Compliant	Yes
Safety Listing	cULus - Listed
California Ban	Lawful for sale
DLC Approved	Yes
Title 20	Exempt
T24/JA8 Compliant	No

© Satco Products, Inc.
All rights reserved 2026