Project / Job Name:

Location:

Fixture Type:

Notes:



65-1700R1 - 2 Foot LED Linear Strip Light; Field Selectable; With Sensor; White Finish

GENERAL

Company	NUVO
EA Height	5.31
EA Width	5.2
EA Length	26.1
Mounting Height	0.06
Bulb Included	Integrated
Material	Steel
Fixture Type	Strip Light
Status	Active
Style	Utility
Surge Protection	Built-in surge protection - 2KV
Total Harmonic Distortion	13.61%
CCT Selectable	Yes
Wattage Selectable	Yes
Finish Family	White
Amps	0.125-0.054/0.167-0.072/0.208-0.090A
Mounting Diameter	4.75
Has Camera	No
Integrated Features	Intergrated MW Sensor
IOT Enabled	No
Lens Finish	White
Lens Material	Polycarbonate (PC)
Photo Cell	Bi-Level Microwave Sensor
Power Factor	0.9
SDS Class	LED_Fixture
Sloped Ceiling Compatible	Yes
Indoor Outdoor	Indoor
Product Technology	LED
Incandescent Equivalent	150W-175W
Serviceable Battery	No
Battery Indicator	No
Digital Display	No

ELECTRICAL

CCT (Kelvin Temp)	3500K/4000K/5000K
Dimmable	Yes-Dimmable
Hours Rated	50000
Beam Angle (degree)	120
Color Temp	Neutral White to Daylight
CRI	80+
Dimming Type	0-10V Dimming, Bi-Level Dimmable
Operating Frequency	50/60Hz
Operating Temp	-4F to +140F (-20C to +60C)
Lumens	1950L-3500L
Volts	120V-277V
Watts	15W/20W/25W
Max Lumens	3500L
Connection	Hardwire

PHYSICAL

Lamp Base	Integrated
Finish	WHITE
ANSI Base	Integrated
Lamp Type	Integrated LED
Mounting Procedure	Ceiling/Wall

ADDITIONAL INFO

Warranty	5-Years

FEATURES

Flicker Free	Yes

PACKAGING

UPC	045923662300
Case Cube	3.9433
Case Height	11.81
Case Length	26.65
Case Quantity	8
Case UPC	10045923662307
Case Weight	15.25
Case Width	21.65
EA Cube	0.4171
EA Height	5.31
EA Length	26.1
EA Quantity	1
EA Weight	1.88
EA Width	5.2
Pack Type	Box
Web Height	3.27
Web Length	24.0
Web Width	2.95

COMPLIANCE

Bug Rating	B1-U3-G1
CA Prop 65	Lead
DLC ID	S-PZ8M6L; S-JF7YDX
FCC Compliant	Yes
IP Rating	IP20
Location Rating	Damp
NSF Approved	No
ROHS Compliant	Yes
Safety Listing	cULus - Certified
California Ban	Lawful for sale
UL Application	Ceiling / Wall
DLC Approved	Yes
Title 20	Exempt
T24/JA8 Compliant	No

© Satco Products, Inc.
All rights reserved 2026