SATCO | NUVO

Project / Job Name:

Location:

Fixture Type:

Notes:

**65-1763** - 20 Watt; 3K/4K/5K CCT Selectable; 2 Light Medium Wall Sconce; Up and Down Installation; Black Finish; 120-277 Volt

WET LOCATION | 90+ CRI | ETL CLASSIFIED Intertek | FC | RoHS COMPLIANT | CCT SELECTABLE | 50,000 HOURS | IP 65

## GENERAL

| | |
|---|---|
| Company | NUVO |
| EA Height | 12.52 |
| EA Width | 5.98 |
| EA Length | 6.02 |
| Mounting Height | 4.45 |
| Mounting Width | 4.56 |
| Bulb Included | Integrated |
| Extends (in) | 5.0 |
| Material | Die-cast Aluminum |
| Fixture Type | Sconce |
| Status | Active |
| Style | Utility |
| Surge Protection | Built-in surge protection - 2KV |
| Total Harmonic Distortion | <20% |
| Up Down Installation | Universal |
| CCT Selectable | Yes |
| Wattage Selectable | No |
| Finish Family | Black |
| Amps | 0.180-0.080A |
| Integrated Features | Integrated Photocell |
| Lens Finish | Clear |
| Lens Material | Glass |
| Lensed | Yes |
| Power Factor | >0.9 |
| SDS Class | LED_Fixture |
| Indoor Outdoor | Outdoor |
| Product Technology | LED |
| Incandescent Equivalent | 100W |
| Serviceable Battery | No |
| Battery Indicator | No |
| Digital Display | No |

## ELECTRICAL

| | |
|---|---|
| CCT (Kelvin Temp) | 3000K/4000K/5000K |
| Dimmable | Non-Dimmable |
| Hours Rated | 50000 |
| Beam Angle (degree) | 50 |
| Color Temp | Soft White to Natural Light |
| CRI | 90+ |
| Operating Frequency | 50/60Hz |
| Operating Temp | -40F to +122F (-40C to +50C) |
| Lumens | 1900L/1800L/1700L |
| Volts | 120V-277V |
| Watts | 20W |
| Max Lumens | 1900L |
| Connection | Hardwire |

## PHYSICAL

| | |
|---|---|
| Lamp Base | Integrated |
| Finish | BLACK |
| Housing Color | Black |
| ANSI Base | Integrated |
| Lamp Type | Integrated LED |
| Fixture Shape | Cylinder |
| Mounting Procedure | Wall |

## ADDITIONAL INFO

| | |
|---|---|
| Warranty | 3-Years |

## PACKAGING

| | |
|---|---|
| UPC | 045923414367 |
| Case Cube | 3.02 |
| Case Height | 13.19 |
| Case Length | 30.91 |
| Case Quantity | 10 |
| Case UPC | 10045923414364 |
| Case Weight | 30.0 |
| Case Width | 12.8 |
| EA Cube | 0.2608 |
| EA Height | 12.52 |
| EA Length | 6.02 |
| EA Quantity | 1 |
| EA Weight | 3.0 |
| EA Width | 5.98 |
| Pack Type | Box |
| Web Height | 11.81 |
| Web Width | 4.57 |

## COMPLIANCE

| | |
|---|---|
| CA Prop 65 | Lead |
| FCC Compliant | Yes |
| IP Rating | IP65 |
| Location Rating | Wet |
| NSF Approved | No |
| ROHS Compliant | Yes |
| Safety Listing | cETLus |
| California Ban | Lawful for sale |
| Title 20 | Exempt |
| T24/JA8 Compliant | No |



© Satco Products, Inc.
All rights reserved 2026