



Project / Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

65-533 - LED Small Flood Light; 15W; 5000K; Bronze Finish



GENERAL

Company	NUVO
EA Height	2.4
EA Width	6.1
EA Length	9.8
Bulb Included	Integrated
Material	Die-cast Aluminum
Fixture Type	Flood Light
Status	Active
Style	Utility
Surge Protection	Built-in surge protection - 2KV
Total Harmonic Distortion	<20%
CCT Selectable	No
Wattage Selectable	No
Finish Family	Bronze
Additional Info	1/2" Thread knuckle mount
Amps	0.150-0.054A
Has Camera	No
IOT Enabled	No
Lens Material	Polycarbonate (PC)
Power Factor	0.9
SDS Class	LED Fixture
Indoor Outdoor	Outdoor
Product Technology	LED
Incandescent Equivalent	50W-100W

ELECTRICAL

CCT (Kelvin Temp)	5000K
Dimmable	Non-Dimmable
Hours Rated	50000
Beam Angle (degree)	110
Color Temp	Natural Light
CRI	80+
Operating Frequency	50/60Hz
Operating Temp	-4F to +113F (-20C to +45C)
HID Equivalent	70W
Lumens	1624L
Volts	120V-277V
Watts	15W

PHYSICAL

Lamp Base	Integrated
Finish	BRONZE
ANSI Base	Integrated
Lamp Type	Integrated LED
Fixture Shape	Rectangle

ADDITIONAL INFO

Warranty	5-Years
----------	---------

PACKAGING

UPC	045923680793
Case Cube	1.5782
Case Height	10.6
Case Length	20.1
Case Quantity	16
Case UPC	10045923680790
Case Weight	20.2
Case Width	12.8
EA Cube	0.083
EA Height	2.4
EA Length	9.8
EA Quantity	1
EA Weight	1.2
EA Width	6.1
Pack Type	Color Box
Web Height	1.5
Web Length	4.33
Web Width	5.35

COMPLIANCE

CA Prop 65	Lead
FCC Compliant	Yes
IC Rated	Yes
IP Rating	IP65
Location Rating	Wet
ROHS Compliant	Yes
Safety Listing	cULus - Certified
California Ban	Lawful for sale
UL Application	Wall
DLC Approved	No
Title 20	Exempt
T24/JA8 Compliant	No