



Project / Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

65-536R1 - LED Medium Flood Light; 30W; 5000K; Bronze Finish; 100V-277V; Dimmable



GENERAL

Company	NUVO
EA Height	11.22
EA Width	2.76
EA Length	9.25
Bulb Included	Integrated
Material	Die-cast Aluminum
Fixture Type	Flood Light
Status	Active
Style	Utility
Surge Protection	Built-in surge protection - 2KV
Total Harmonic Distortion	15%
CCT Selectable	No
Wattage Selectable	No
Finish Family	Bronze
Additional Info	1/2" Thread knuckle mount
Amps	0.250-0.108A
Has Camera	No
IOT Enabled	No
Lens Finish	Translucent
Lens Material	Polycarbonate (PC)
Power Factor	0.9
SDS Class	LED Fixture
Indoor Outdoor	Outdoor
Product Technology	LED
Incandescent Equivalent	100W-150W

ELECTRICAL

CCT (Kelvin Temp)	5000K
Dimmable	Yes-Dimmable
Hours Rated	50000
Beam Angle (degree)	110x110
Color Temp	Natural Light
CRI	80+
Dimming Type	0-10V Dimming
Operating Frequency	50/60Hz
Operating Temp	-22F to +113F (-30C to +45C)
Lumens	4035L
Volts	120V-277V
Watts	30W

PHYSICAL

Lamp Base	Integrated
Finish	BRONZE
ANSI Base	Integrated
Lamp Type	Integrated LED
Fixture Shape	Rectangle

ADDITIONAL INFO

Warranty	5-Years
----------	---------

PACKAGING

UPC	045923658655
Case Cube	1.5682
Case Height	12.01
Case Length	19.17
Case Quantity	8
Case UPC	10045923658652
Case Weight	26.8
Case Width	11.77
EA Cube	0.1658
EA Height	11.22
EA Length	9.25
EA Quantity	1
EA Weight	3.1
EA Width	2.76
Pack Type	Color Box
Web Height	1.77
Web Length	7.17
Web Width	8.58

COMPLIANCE

Bug Rating	B2-U0-G0
CA Prop 65	Lead
DLC ID	S-L0IZ1Y
FCC Compliant	Yes
IC Rated	Yes
IP Rating	IP65
Location Rating	Wet
NSF Approved	No
ROHS Compliant	Yes
Safety Listing	cULus - Certified
California Ban	Lawful for sale
DLC Approved	Yes
Title 20	Exempt
T24/JA8 Compliant	No