SATCO | NUVO

Project / Job Name:

Location:

Fixture Type:

Notes:

65-575R1 - LED Emergency Backlit Flat Panel; 2 ft. x 2 ft.; Wattage and CCT Selectable; 120-277 Volt; ColorQuick Technology; PowerQuick Technology; White Finish

DAMP LOCATION · DIMMABLE · ETL · FC · RoHS · CCT SELECTABLE · 50,000 HOURS · 5 YEAR WARRANTY · 120-277V · IP 20 · IC RATED · NSF · 0-10V DIMMING · TITLE 20

GENERAL

Company	NUVO
EA Height	25.2
EA Width	4.33
EA Length	25.0
Bulb Included	Integrated
Material	Aluminum / Steel
Fixture Type	Backlit Flat Panel
Status	Active
Style	Utility
Surge Protection	Built-in surge protection - 2KV
Total Harmonic Distortion	16.30%
Wire Color	White / Black / Green
Wire Length	3.54
CCT Selectable	Yes
Wattage Selectable	Yes
Finish Family	White
Additional Info	Driver Specs - VDC38-48V; 430/620/810mA
Amps	0.200-0.072/0.300-0.108/0.400-0.144A
Has Camera	No
Integrated Features	Integrated Battery Backup
IOT Enabled	No
Lens Finish	Frost
Lens Material	Poly methyl methacrylate (PMMA)
Photo Cell	No Photocell
Power Factor	0.9
SDS Class	LED_Fixture
Indoor Outdoor	Indoor
Product Technology	LED
Incandescent Equivalent	150W-175W
Serviceable Battery	No
Battery Indicator	No
Digital Display	No

ELECTRICAL

CCT (Kelvin Temp)	3500K/4000K/5000K
Dimmable	Yes-Dimmable
Hours Rated	50000
Beam Angle (degree)	120
Color Temp	Warm to Cool White
CRI	80+
Dimming Type	0-10V Dimming
Operating Frequency	50/60Hz
Operating Temp	+1.4F to +113F (-17C to +45C)
Lumens	2200L-4600L
Volts	120V-277V
Watts	20W/30W/40W
Max Lumens	4600L
Connection	Hardwire
Battery Chemistry	Lithium-ion (Li-ion)

PHYSICAL

Lamp Base	Integrated
Finish	WHITE
ANSI Base	Integrated
Lamp Type	Integrated LED
Fixture Shape	Square
Mounting Procedure	Ceiling

ADDITIONAL INFO

Warranty	5-Years

FEATURES

Flicker Free	Yes

PACKAGING

UPC	045923657177
Case Cube	1.5786
Case Height	25.2
Case Length	25.0
Case Quantity	1
Case UPC	10045923657174
Case Weight	9.59
Case Width	4.33
EA Cube	1.5786
EA Height	25.2
EA Length	25.0
EA Quantity	1
EA Weight	9.59
EA Width	4.33
Pack Type	Box
Web Height	3.06
Web Length	23.75
Web Width	23.75

COMPLIANCE

Air Tight	No
CA Prop 65	Lead
DLC ID	S-QWKSLT; S-JP9ZK5
FCC Compliant	Yes
IC Rated	Yes
IP Rating	IP20
Location Rating	Damp
NSF Approved	Yes
ROHS Compliant	Yes
Safety Listing	cETLus - Listed
California Ban	Lawful for sale
UL Application	LED Panel Luminaire
DLC Approved	Yes
Title 20	Yes
T24/JA8 Compliant	No

© Satco Products, Inc.
All rights reserved 2026