SATCO | NUVO

Project / Job Name:

Location:

Fixture Type:

Notes:

65-576R1 - LED Emergency Backlit Flat Panel; 2 ft. x 4 ft.; Wattage and CCT Selectable; 120-277 Volt; ColorQuick Technology; PowerQuick Technology; White Finish

DAMP LOCATION · DIMMABLE · ETL · FC · RoHS · CCT SELECTABLE · 50,000 HOURS · 5 YEAR WARRANTY · 120-277V · IP 20 · IC RATED · NSF · 0-10V DIMMING · TITLE 20

GENERAL

Company	NUVO
EA Height	25.2
EA Width	4.33
EA Length	49.02
Bulb Included	Integrated
Material	Aluminum / Steel
Fixture Type	Backlit Flat Panel
Status	Active
Style	Utility
Surge Protection	Built-in surge protection - 2KV
Total Harmonic Distortion	9.70%
Wire Color	White / Black / Green
Wire Length	3.54
CCT Selectable	Yes
Wattage Selectable	Yes
Finish Family	White
Additional Info	Driver Specs - VDC38-48V; 630/810/1030mA
Amps	0.300-0.108/0.400-0.144/0.500-0.181A
Has Camera	No
Integrated Features	Integrated Battery Backup
IOT Enabled	No
Lens Finish	Frost
Lens Material	Poly methyl methacrylate (PMMA)
Photo Cell	No Photocell
Power Factor	0.9
SDS Class	LED_Fixture
Indoor Outdoor	Indoor
Product Technology	LED
Incandescent Equivalent	150W-175W
Serviceable Battery	No
Battery Indicator	No
Digital Display	No

ELECTRICAL

CCT (Kelvin Temp)	3500K/4000K/5000K
Dimmable	Yes-Dimmable
Hours Rated	50000
Beam Angle (degree)	120
Color Temp	Warm to Cool White
CRI	80+
Dimming Type	0-10V Dimming
Operating Frequency	50/60Hz
Operating Temp	+1.4F to +113F (-17C to +45C)
Lumens	3300L-5750L
Volts	120V-277V
Watts	30W/40W/50W
Max Lumens	5750L
Connection	Hardwire
Battery Chemistry	Lithium-ion (Li-ion)

PHYSICAL

Lamp Base	Integrated
Finish	WHITE
ANSI Base	Integrated
Lamp Type	Integrated LED
Fixture Shape	Rectangle
Mounting Procedure	Ceiling

ADDITIONAL INFO

Warranty	5-Years

FEATURES

Flicker Free	Yes

PACKAGING

UPC	045923657184
Case Cube	3.0954
Case Height	25.2
Case Length	49.02
Case Quantity	1
Case UPC	10045923657181
Case Weight	15.33
Case Width	4.33
EA Cube	3.0954
EA Height	25.2
EA Length	49.02
EA Quantity	1
EA Weight	15.33
EA Width	4.33
Pack Type	Box
Web Height	3.06
Web Length	47.72
Web Width	23.75

COMPLIANCE

Air Tight	No
CA Prop 65	Lead
DLC ID	S-BPMTYH; S-C51JHR
FCC Compliant	Yes
IC Rated	Yes
IP Rating	IP20
Location Rating	Damp
NSF Approved	Yes
ROHS Compliant	Yes
Safety Listing	cETLus - Listed
California Ban	Lawful for sale
UL Application	LED Panel Luminaire
DLC Approved	Yes
Title 20	Yes
T24/JA8 Compliant	No

© Satco Products, Inc.
All rights reserved 2026