



Project / Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

65-581 - LED Backlit Flat Panel; 40 Watt; 2 ft. x 2 ft.; Selectable CCT; 100-347 Volt



GENERAL

Company	NUVO
EA Height	25.2
EA Width	2.56
EA Length	25.0
Bulb Included	Integrated
Dimmable Text	0-10V Dimming
Material	Aluminum / Steel
Fixture Type	Backlit Flat Panel
Status	Discontinued
Style	Utility
Surge Protection	Built-in surge protection - 2KV
Total Harmonic Distortion	20%
Wire Color	White / Black / Green
Wire Length	3.54
CCT Selectable	Yes
Wattage Selectable	No
Finish Family	White
Amps	0.400-0.115A
Has Camera	No
IOT Enabled	No
Lens Finish	Frost
Lens Material	Poly methyl methacrylate (PMMA)
Photo Cell	No Photocell
Power Factor	0.9
SDS Class	LED_Fixture
Indoor Outdoor	Indoor
Product Technology	LED
Incandescent Equivalent	200W

ELECTRICAL

CCT (Kelvin Temp)	3500K/4000K/5000K
Dimmable	Yes-Dimmable
Hours Rated	50000
Beam Angle (degree)	120
Color Temp	Warm to Cool White
CRI	80+
Dimming Type	0-10V Dimming
Operating Frequency	50/60Hz
Operating Temp	-17C (+1.4F) to +45C (+113F)
Lumens	4400L-4600L
Volts	120V-347V
Watts	40W

PHYSICAL

Lamp Base	Integrated
Finish	WHITE
ANSI Base	Integrated
Lamp Type	Integrated LED
Fixture Shape	Square

ADDITIONAL INFO

Warranty	5-Years
----------	---------

FEATURES

Flicker Free	Yes
--------------	-----

PACKAGING

UPC	045923659522
Case Cube	0.9333
Case Height	25.2
Case Length	25.0
Case Quantity	1
Case UPC	10045923659529
Case Weight	6.5
Case Width	2.56
EA Cube	0.9333
EA Height	25.2
EA Length	25.0
EA Quantity	1
EA Weight	6.5
EA Width	2.56
Pack Type	Box
Web Height	1.5
Web Length	23.75
Web Width	23.75

COMPLIANCE

Air Tight	No
CA Prop 65	Lead
DLC ID	PLGZ80J3A5E0
FCC Compliant	Yes
IC Rated	Yes
IP Rating	IP20
Location Rating	Damp
NSF Approved	Yes
ROHS Compliant	Yes
Safety Listing	cETLus - Listed
California Ban	Lawful for sale
UL Application	LED Panel Luminaire
DLC Approved	Yes
Title 20	Exempt
T24 Compliant	No