



Project / Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

65-583 - LED Backlit Flat Panel; 40 Watt; 1 ft. x 4 ft.; CCT Selectable ; 100-347 Volt



GENERAL

| | |
|---------------------------|---------------------------------|
| Company | NUVO |
| EA Height | 13.39 |
| EA Width | 2.56 |
| EA Length | 49.02 |
| Bulb Included | Integrated |
| Material | Aluminum / Steel |
| Fixture Type | Flat Panel |
| Status | Discontinued |
| Style | Utility |
| Surge Protection | Built-in surge protection - 2KV |
| Total Harmonic Distortion | 20.40% |
| Wire Color | White / Black / Green |
| Wire Length | 3.54 |
| CCT Selectable | Yes |
| Wattage Selectable | No |
| Finish Family | White |
| Amps | 0.400-0.115A |
| Has Camera | No |
| IOT Enabled | No |
| Lens Finish | Frost |
| Lens Material | Poly methyl methacrylate (PMMA) |
| Photo Cell | No Photocell |
| Power Factor | 0.9 |
| SDS Class | LED_Fixture |
| Indoor Outdoor | Indoor |
| Product Technology | LED |
| Incandescent Equivalent | 200W |

ELECTRICAL

| | |
|---------------------|-------------------------------|
| CCT (Kelvin Temp) | 3500K/4000K/5000K |
| Dimmable | Yes-Dimmable |
| Hours Rated | 50000 |
| Beam Angle (degree) | 120 |
| Color Temp | Warm to Cool White |
| CRI | 80+ |
| Dimming Type | 0-10V Dimming |
| Operating Frequency | 50/60Hz |
| Operating Temp | +1.4F to +113F (-17C to +45C) |
| Lumens | 4400L-4600L |
| Volts | 120V-347V |
| Watts | 40W |

PHYSICAL

| | |
|---------------|----------------|
| Lamp Base | Integrated |
| Finish | WHITE |
| ANSI Base | Integrated |
| Lamp Type | Integrated LED |
| Fixture Shape | Rectangle |

ADDITIONAL INFO

| | |
|----------|---------|
| Warranty | 5-Years |
|----------|---------|

FEATURES

| | |
|--------------|-----|
| Flicker Free | Yes |
|--------------|-----|

PACKAGING

| | |
|---------------|----------------|
| UPC | 045923650789 |
| Case Cube | 0.9724 |
| Case Height | 13.39 |
| Case Length | 49.02 |
| Case Quantity | 1 |
| Case UPC | 10045923650786 |
| Case Weight | 6.7 |
| Case Width | 2.56 |
| EA Cube | 0.9724 |
| EA Height | 13.39 |
| EA Length | 49.02 |
| EA Quantity | 1 |
| EA Weight | 6.7 |
| EA Width | 2.56 |
| Pack Type | Box |
| Web Height | 1.5 |
| Web Length | 47.72 |
| Web Width | 11.84 |

COMPLIANCE

| | |
|-------------------|---------------------|
| Air Tight | No |
| CA Prop 65 | Lead |
| DLC ID | PLOANBILZL75 |
| FCC Compliant | Yes |
| IC Rated | Yes |
| IP Rating | IP20 |
| Location Rating | Damp |
| NSF Approved | Yes |
| ROHS Compliant | Yes |
| Safety Listing | cETLus - Listed |
| California Ban | Lawful for sale |
| UL Application | LED Panel Luminaire |
| DLC Approved | Yes |
| Title 20 | Exempt |
| T24/JA8 Compliant | No |