SATCO | NUVO

Project / Job Name:

Location:

Fixture Type:

Notes:



**65-585** - LED Emergency Backlit Flat Panel; 40 Watt; 2 ft. x 2 ft.; Selectable CCT; 100-347 Volt

DAMP LOCATION · DIMMABLE · ETL · FC · RoHS · CCT SELECTABLE · 50,000 HOURS · 5 YEAR WARRANTY · IP 20 · IC RATED · NSF · 0-10V DIMMING

## GENERAL

| | |
|---|---|
| Generational SKU | 65-585R1 |
| Company | NUVO |
| EA Height | 25.2 |
| EA Width | 4.33 |
| EA Length | 25.0 |
| Bulb Included | Integrated |
| Material | Aluminum / Steel |
| Fixture Type | Backlit Flat Panel |
| Status | Obsolete |
| Style | Utility |
| Surge Protection | Built-in surge protection - 2KV |
| Total Harmonic Distortion | 19.20% |
| Wire Color | White / Black / Green |
| Wire Length | 3.54 |
| CCT Selectable | Yes |
| Wattage Selectable | No |
| Finish Family | White |
| Amps | 0.400-0.115A |
| Has Camera | No |
| IOT Enabled | No |
| Lens Finish | Frost |
| Lens Material | Poly methyl methacrylate (PMMA) |
| Photo Cell | No Photocell |
| Power Factor | 0.9 |
| SDS Class | LED_Fixture |
| Indoor Outdoor | Indoor |
| Product Technology | LED |
| Incandescent Equivalent | 200W |
| Serviceable Battery | No |
| Battery Indicator | No |
| Digital Display | No |

## ELECTRICAL

| | |
|---|---|
| CCT (Kelvin Temp) | 3500K/4000K/5000K |
| Dimmable | Yes-Dimmable |
| Hours Rated | 50000 |
| Beam Angle (degree) | 120 |
| Color Temp | Warm to Cool White |
| CRI | 80+ |
| Dimming Type | 0-10V Dimming |
| Operating Frequency | 50/60Hz |
| Operating Temp | +1.4F to +113F (-17C to +45C) |
| Lumens | 4400L-4600L |
| Volts | 120V-347V |
| Watts | 40W |
| Max Lumens | 4600L |
| Connection | Hardwire |
| Battery Chemistry | Lithium-ion (Li-ion) |

## PHYSICAL

| | |
|---|---|
| Lamp Base | Integrated |
| Finish | WHITE |
| ANSI Base | Integrated |
| Lamp Type | Integrated LED |
| Fixture Shape | Square |
| Mounting Procedure | Ceiling |

## ADDITIONAL INFO

| | |
|---|---|
| Warranty | 5-Years |

## FEATURES

| | |
|---|---|
| Flicker Free | Yes |

## PACKAGING

| | |
|---|---|
| UPC | 045923659560 |
| Case Cube | 1.5786 |
| Case Height | 25.2 |
| Case Length | 25.0 |
| Case Quantity | 1 |
| Case UPC | 10045923659567 |
| Case Weight | 9.59 |
| Case Width | 4.33 |
| EA Cube | 1.5786 |
| EA Height | 25.2 |
| EA Length | 25.0 |
| EA Quantity | 1 |
| EA Weight | 9.59 |
| EA Width | 4.33 |
| Pack Type | Box |
| Web Height | 2.88 |
| Web Length | 23.75 |
| Web Width | 23.75 |

## COMPLIANCE

| | |
|---|---|
| Air Tight | No |
| CA Prop 65 | Lead |
| DLC ID | PLXWJELBYVI9 |
| FCC Compliant | Yes |
| IC Rated | Yes |
| IP Rating | IP20 |
| Location Rating | Damp |
| NSF Approved | Yes |
| ROHS Compliant | Yes |
| Safety Listing | cETLus - Listed |
| California Ban | Non-Compliant |
| UL Application | LED Panel Luminaire |
| DLC Approved | Yes |
| Title 20 | No |
| T24/JA8 Compliant | No |



© Satco Products, Inc.
All rights reserved 2026