



Project / Job Name: \_\_\_\_\_

Location: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Notes: \_\_\_\_\_

**65-586** - LED Emergency Backlit Flat Panel; 50 Watt; 2 ft. x 4 ft.; Selectable CCT; 100-347 Volt



**GENERAL**

Company	NUVO
EA Height	25.2
EA Width	4.33
EA Length	49.02
Bulb Included	Integrated
Material	Aluminum / Steel
Fixture Type	Backlit Flat Panel
Status	Discontinued
Style	Utility
Surge Protection	Built-in surge protection - 2KV
Total Harmonic Distortion	20%
Wire Color	White / Black / Green
Wire Length	3.54
CCT Selectable	Yes
Wattage Selectable	No
Finish Family	White
Amps	0.500-0.144A
Has Camera	No
IOT Enabled	No
Lens Finish	Frost
Lens Material	Poly methyl methacrylate (PMMA)
Photo Cell	No Photocell
Power Factor	0.9
SDS Class	LED_Fixture
Indoor Outdoor	Indoor
Product Technology	LED
Incandescent Equivalent	250W

**ELECTRICAL**

CCT (Kelvin Temp)	3500K/4000K/5000K
Dimmable	Yes-Dimmable
Hours Rated	50000
Beam Angle (degree)	120
Color Temp	Warm to Cool White
CRI	80+
Dimming Type	0-10V Dimming
Operating Frequency	50/60Hz
Operating Temp	+1.4F to +113F (-17C to +45C)
Lumens	5500L-5750L
Volts	120V-347V
Watts	50W

**PHYSICAL**

Lamp Base	Integrated
Finish	WHITE
ANSI Base	Integrated
Lamp Type	Integrated LED
Fixture Shape	Square

**ADDITIONAL INFO**

Warranty	5-Years
----------	---------

**FEATURES**

Flicker Free	Yes
--------------	-----

**PACKAGING**

UPC	045923659577
Case Cube	3.0954
Case Height	25.2
Case Length	49.02
Case Quantity	1
Case UPC	10045923659574
Case Weight	15.33
Case Width	4.33
EA Cube	3.0954
EA Height	25.2
EA Length	49.02
EA Quantity	1
EA Weight	15.33
EA Width	4.33
Pack Type	Box
Web Height	2.88
Web Length	47.72
Web Width	23.75

**COMPLIANCE**

Air Tight	No
CA Prop 65	Lead
DLC ID	PL986P3MZCPN
FCC Compliant	Yes
IC Rated	Yes
IP Rating	IP20
Location Rating	Damp
NSF Approved	Yes
ROHS Compliant	Yes
Safety Listing	cETLus - Listed
California Ban	Non-Compliant
UL Application	LED Panel Luminaire
DLC Approved	Yes
Title 20	No
T24/JA8 Compliant	No