



Project / Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

65-615 - LED Flood Light; 70 Watt; 4000K; Bronze Finish



GENERAL

Company	NUVO
EA Height	4.13
EA Width	13.78
EA Length	12.99
Bulb Included	Integrated
Dimmable Text	0-10V Dimming Only
Material	Aluminum Alloy
Fixture Type	Flood Light
Status	Active
Style	Utility
Surge Protection	Built-in surge protection - 6KV
Total Harmonic Distortion	15%
Wire Color	White / Black / Green / Gray / Yellow
Wire Length	19.69
Wire Quantity	5
CCT Selectable	No
Wattage Selectable	No
Finish Family	Bronze
Amps	0.583-0.253A
Has Camera	No
IOT Enabled	No
Lens Finish	Frost
Lens Material	Polycarbonate (PC)
Power Factor	0.9
SDS Class	LED_Fixture
Indoor Outdoor	Outdoor
Product Technology	LED
Incandescent Equivalent	200W-250W

ELECTRICAL

CCT (Kelvin Temp)	4000K
Dimmable	Yes-Dimmable
Hours Rated	50000
Beam Angle (degree)	150
Color Temp	Cool White
CRI	80+
Dimming Type	0-10V Dimming
Operating Frequency	50-60Hz
Operating Temp	-40C (-40F) to +50C (+122F)
Lumens	9889L
Volts	120V-277V
Watts	70W

PHYSICAL

Lamp Base	Integrated
Finish	BRONZE
ANSI Base	Integrated
Lamp Type	Integrated LED
Fixture Shape	Rectangle

ADDITIONAL INFO

Warranty	5-Years
----------	---------

PACKAGING

UPC	045923674167
Case Cube	2.479
Case Height	14.57
Case Length	21.65
Case Quantity	5
Case UPC	10045923674164
Case Weight	32.56
Case Width	13.58
EA Cube	0.4278
EA Height	4.13
EA Length	12.99
EA Quantity	1
EA Weight	6.16
EA Width	13.78
Pack Type	Box
Web Height	2.25
Web Length	10.44
Web Width	11.5

COMPLIANCE

Bug Rating	B3-U3-G2
CA Prop 65	Lead
DLC ID	PLUEBIWOZFG7
FCC Compliant	Yes
IC Rated	Yes
IP Rating	IP65
Location Rating	Wet
ROHS Compliant	Yes
Safety Listing	cULus - Certified
California Ban	Lawful for sale
UL Application	Outdoor
DLC Approved	Yes
Energy Star Certified	No
Title 20	Exempt
T24 Compliant	No