



Project / Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

65-616 - LED Flood Light; 70 Watt; 5000K; Bronze Finish



GENERAL

Company	NUVO
EA Height	4.13
EA Width	13.78
EA Length	12.99
Bulb Included	Integrated
Material	Aluminum Alloy
Fixture Type	Flood Light
Includes	Mounting Plate
Status	Active
Style	Utility
Surge Protection	Built-in surge protection - 6KV
Total Harmonic Distortion	15%
Wire Color	White / Black / Green / Gray / Yellow
Wire Length	19.69
Wire Quantity	5
CCT Selectable	No
Wattage Selectable	No
Finish Family	Bronze
Amps	0.583-0.253A
Has Camera	No
IOT Enabled	No
Lens Finish	Frost
Lens Material	Polycarbonate (PC)
Power Factor	0.9
SDS Class	LED_Fixture
Indoor Outdoor	Outdoor
Product Technology	LED
Incandescent Equivalent	200W-250W

ELECTRICAL

CCT (Kelvin Temp)	5000K
Dimmable	Yes-Dimmable
Hours Rated	50000
Beam Angle (degree)	150
Color Temp	Natural Light
CRI	80+
Dimming Type	0-10V Dimming
Operating Frequency	50-60Hz
Operating Temp	-40F to +122F (-40C to +50C)
Lumens	10030L
Volts	120V-277V
Watts	70W

PHYSICAL

Lamp Base	Integrated
Finish	BRONZE
ANSI Base	Integrated
Lamp Type	Integrated LED
Fixture Shape	Rectangle

ADDITIONAL INFO

Warranty	5-Years
----------	---------

PACKAGING

UPC	045923674174
Case Cube	2.479
Case Height	14.57
Case Length	21.65
Case Quantity	5
Case UPC	10045923674171
Case Weight	32.56
Case Width	13.58
EA Cube	0.4278
EA Height	4.13
EA Length	12.99
EA Quantity	1
EA Weight	6.16
EA Width	13.78
Pack Type	Box
Web Height	2.25
Web Length	10.44
Web Width	11.5

COMPLIANCE

Bug Rating	B3-U3-G2
CA Prop 65	Lead
DLC ID	PLND67ZISYJI
FCC Compliant	Yes
IC Rated	Yes
IP Rating	IP65
Location Rating	Wet
ROHS Compliant	Yes
Safety Listing	cULus - Certified
California Ban	Lawful for sale
UL Application	Outdoor
DLC Approved	Yes
Title 20	Exempt
T24/JA8 Compliant	No