



Project / Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

65-632R1 - LED Canopy Fixture; 100 Watt; CCT Selectable; Bronze Finish



GENERAL

| | |
|---------------------------|------------------------------------|
| Company | NUVO |
| EA Height | 5.51 |
| EA Width | 12.8 |
| EA Length | 12.8 |
| Bulb Included | Integrated |
| Diameter | 11.02 |
| Dimmable Text | 0-10V Dimming |
| Material | Die-cast Aluminum |
| Fixture Type | Canopy |
| Product Notes | UV Stabilized Powder Coated Finish |
| Status | Active |
| Style | Utility |
| Surge Protection | Built-in surge protection - 6KV |
| Total Harmonic Distortion | <20% |
| CCT Selectable | Yes |
| Wattage Selectable | No |
| Finish Family | Bronze |
| Amps | 0.833-0.361A |
| Has Camera | No |
| IOT Enabled | No |
| Lens Material | Polycarbonate (PC) |
| Photo Cell | Optional Add-On |
| Power Factor | >0.9 |
| SDS Class | LED_Fixture |
| Indoor Outdoor | Outdoor |
| Product Technology | LED |
| Incandescent Equivalent | 500W |

ELECTRICAL

| | |
|---------------------|-----------------------------|
| CCT (Kelvin Temp) | 3000K/4000K/5000K |
| Dimmable | Yes-Dimmable |
| Hours Rated | 50000 |
| Beam Angle (degree) | 150 |
| Color Temp | Warm to Cool White |
| CRI | 80+ |
| Dimming Type | 0-10V Dimming |
| Operating Frequency | 50/60Hz |
| Operating Temp | -40C (-40F) to +45C (+113F) |
| Lumens | 14298L/15322/14943L |
| Volts | 120V-277V |
| Watts | 100W |

PHYSICAL

| | |
|---------------|----------------|
| Lamp Base | Integrated |
| Finish | BRONZE |
| ANSI Base | Integrated |
| Lamp Type | Integrated LED |
| Fixture Shape | Round |

ADDITIONAL INFO

| | |
|----------|---------|
| Warranty | 5-Years |
|----------|---------|

PACKAGING

| | |
|----------------|----------------|
| UPC | 045923652851 |
| Case Cube | 1.2604 |
| Case Height | 13.58 |
| Case Length | 13.58 |
| Case Quantity | 2 |
| Case UPC | 10045923652858 |
| Case Weight | 19.8 |
| Case Width | 11.81 |
| EA Cube | 0.5224 |
| EA Height | 5.51 |
| EA Length | 12.8 |
| EA Quantity | 1 |
| EA Weight | 8.8 |
| EA Width | 12.8 |
| Inner Cube | 0.0 |
| Inner Height | 0.0 |
| Inner Length | 0.0 |
| Inner Quantity | 0 |
| Inner Weight | 0.0 |
| Inner Width | 0.0 |
| Pack Type | Box |
| Web Height | 3.15 |
| Web Width | 11.02 |

COMPLIANCE

| | |
|-----------------------|-------------------|
| Bug Rating | B3-U3-G2 |
| CA Prop 65 | Lead |
| DLC ID | S-ZW3LNP |
| FCC Compliant | Yes |
| IP Rating | IP65 |
| Location Rating | Wet |
| ROHS Compliant | Yes |
| Safety Listing | cULus - Certified |
| California Ban | Lawful for sale |
| DLC Approved | Yes |
| Energy Star Certified | No |
| Title 20 | Exempt |
| T24 Compliant | No |