



Project / Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

65-661 - LED Gooseneck; 30W/40W/50W; CCT Selectable 3K/4K/5K; Black; 120-277V; With Photocell



GENERAL

Company	NUVO
EA Height	10.04
EA Width	16.14
EA Length	20.28
Bulb Included	Integrated
Diameter	14.17
Dimmable Text	0-10V Dimming
Extends (in)	23.23
Material	Die-cast Aluminum
Fixture Type	Gooseneck
Includes	16 Inch Mounting Arm
Status	Active
Style	Traditional
Surge Protection	Built-in surge protection - 2KV
Total Harmonic Distortion	5.20%
CCT Selectable	Yes
Wattage Selectable	Yes
Finish Family	Black
Additional Info	UV Powder Coated Finish
Amps	0.250-0.108/0.333-0.144/0.417-0.181A
Mounting Diameter	4.65
Has Camera	No
Integrated Features	Integrated Photocell
IOT Enabled	No
Lens Finish	Clear
Lens Material	Polycarbonate (PC)
Photo Cell	Has Photocell
Power Factor	>0.9
SDS Class	LED_Fixture
Indoor Outdoor	Outdoor
Product Technology	LED
Incandescent Equivalent	250W/300W/400W

PACKAGING

UPC	045923656613
Case Cube	1.9018
Case Height	10.04
Case Length	20.28
Case Quantity	1
Case UPC	10045923656610
Case Weight	5.1
Case Width	16.14
EA Cube	1.9018
EA Height	10.04
EA Length	20.28
EA Quantity	1
EA Weight	5.1
EA Width	16.14
Pack Type	Box
Web Height	14.96
Web Width	14.17

COMPLIANCE

ADA Compliant	No
Bug Rating	B2-U2-G0
CA Prop 65	Lead
DLC ID	S-85IVYA
FCC Compliant	Yes
IP Rating	IP65
Location Rating	Wet
ROHS Compliant	Yes
Safety Listing	cETLus - Listed
California Ban	Lawful for sale
DLC Approved	Yes
Title 20	Exempt
T24 Compliant	No

ELECTRICAL

CCT (Kelvin Temp)	3000K/4000K/5000K
Dimmable	Yes-Dimmable
Hours Rated	50000
Beam Angle (degree)	100
Color Temp	Warm to Cool White
CRI	80+
Dimming Type	0-10V Dimming
Operating Frequency	50/60Hz
Operating Temp	-22F (-30C) to +122F (+50C)
Lumens	3300L-5500L
Volts	120V-277V
Watts	30W/40W/50W

PHYSICAL

Lamp Base	Integrated
Finish	BLACK
ANSI Base	Integrated
Lamp Type	Integrated LED

ADDITIONAL INFO

Warranty	5-Years
----------	---------