Project / Job Name:

Location:

Fixture Type:

Notes:



**65-695** - 2X4 Double Basket LED Troffer Fixture; Wattage Selectable; CCT Selectable; Lumens Selectable; 100-277V; White Finish

DAMP LOCATION · DIMMABLE · FC · RoHS COMPLIANT · CCT SELECTABLE · 50,000 HOURS · 5 YEAR WARRANTY · 120-277V · IP 20 · IC RATED · 0-10V DIMMING

## GENERAL

| | |
|---|---|
| Company | NUVO |
| EA Height | 25.67 |
| EA Width | 3.27 |
| EA Length | 49.49 |
| Bulb Included | Integrated |
| Material | Steel |
| Fixture Type | Double Basket Troffer |
| Status | Active |
| Style | Utility |
| Surge Protection | Built-in surge protection - 2KV |
| Total Harmonic Distortion | <20% |
| CCT Selectable | Yes |
| Wattage Selectable | Yes |
| Finish Family | White |
| Amps | 0.300-0.108/0.400-0.144/0.500-0.181A |
| Has Camera | No |
| IOT Enabled | No |
| Lens Material | Poly methyl methacrylate (PMMA) |
| Power Factor | 0.9 |
| SDS Class | LED_Fixture |
| Indoor Outdoor | Indoor |
| Product Technology | LED |
| Incandescent Equivalent | 125W |
| Serviceable Battery | No |
| Battery Indicator | No |
| Digital Display | No |

## ELECTRICAL

| | |
|---|---|
| CCT (Kelvin Temp) | 3500K/4000K/5000K |
| Dimmable | Yes-Dimmable |
| Hours Rated | 50000 |
| Beam Angle (degree) | 120 |
| Color Temp | Warm to Cool White |
| CRI | 80+ |
| Dimming Type | 0-10V Dimming |
| Operating Frequency | 50/60Hz |
| Operating Temp | -4F to +104F (-20C to +40C) |
| HID Equivalent | 70W-125W |
| Lumens | 3300L-5750L |
| Volts | 120V-277V |
| Watts | 30W/40W/50W |
| Max Lumens | 5750L |
| Connection | Hardwire |

## PHYSICAL

| | |
|---|---|
| Lamp Base | Integrated |
| Finish | WHITE |
| ANSI Base | Integrated |
| Lamp Type | Integrated LED |
| Fixture Shape | Rectangle |
| Mounting Procedure | Ceiling |

## ADDITIONAL INFO

| | |
|---|---|
| Warranty | 5-Years |

## FEATURES

| | |
|---|---|
| Flicker Free | Yes |

## PACKAGING

| | |
|---|---|
| UPC | 045923655203 |
| Case Cube | 2.4041 |
| Case Height | 25.67 |
| Case Length | 49.49 |
| Case Quantity | 1 |
| Case UPC | 10045923655200 |
| Case Weight | 16.1 |
| Case Width | 3.27 |
| EA Cube | 2.4041 |
| EA Height | 25.67 |
| EA Length | 49.49 |
| EA Quantity | 1 |
| EA Weight | 16.1 |
| EA Width | 3.27 |
| Pack Type | Box |
| Web Height | 2.61 |
| Web Length | 47.72 |
| Web Width | 23.74 |

## COMPLIANCE

| | |
|---|---|
| CA Prop 65 | Lead |
| DLC ID | S-MTPRWN |
| FCC Compliant | Yes |
| IC Rated | Yes |
| IP Rating | IP20 |
| Location Rating | Damp |
| ROHS Compliant | Yes |
| Safety Listing | cULus - Certified |
| California Ban | Lawful for sale |
| UL Application | LED Recessed Luminaire/Type IC |
| DLC Approved | Yes |
| Title 20 | Exempt |
| T24/JA8 Compliant | No |



© Satco Products, Inc.
All rights reserved 2026