



Project / Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

65-728 - 30 Watt LED DOB Tempered Glass Flood Light; 5000K CCT; Bronze Finish



GENERAL	
Company	SATCO
EA Height	9.57
EA Width	8.27
EA Length	2.24
Bulb Included	Integrated
Material	Die-cast Aluminum
Fixture Type	Flood Light
Includes	Yoke Mount
Product Notes	NEMA Distribution: 6Vx6H (120x120)
Status	Active
Surge Protection	Built-in surge protection - 2KV
Total Harmonic Distortion	<30%
Up Down Installation	Up
CCT Selectable	No
Wattage Selectable	No
Finish Family	Bronze
Amps	0.250A
Integrated Features	Integrated Heat Sink For Thermal Management; 1/2 Inch Knuckle Mount
Lens Finish	Clear
Lens Material	Tempered Glass
Lensed	Yes
Power Factor	>0.94
SDS Class	LED_Fixture
Indoor Outdoor	Outdoor
Product Technology	LED
Incandescent Equivalent	200W

ELECTRICAL	
CCT (Kelvin Temp)	5000K
Dimmable	Non-Dimmable
Hours Rated	30000
Beam Angle (degree)	120
Color Temp	Natural Light
CRI	80+
Operating Frequency	50/60Hz
Operating Temp	-22F to +113F (-30C to +45C)
Lumens	3450L
Volts	120v
Watts	30W

PHYSICAL	
Lamp Base	Integrated
Finish	BRONZE
ANSI Base	Integrated
Lamp Type	Integrated LED
Fixture Shape	Rectangle

ADDITIONAL INFO	
Warranty	3-Years

FEATURES	
Flicker Free	No

PACKAGING	
UPC	045923410949
Case Cube	1.9317
Case Height	10.31
Case Length	17.13
Case Quantity	16
Case UPC	10045923410946
Case Weight	28.0
Case Width	18.9
EA Cube	0.1026
EA Height	9.57
EA Length	2.24
EA Quantity	1
EA Weight	1.63
EA Width	8.27
Pack Type	Color Box
Web Height	7.4
Web Width	5.97

COMPLIANCE	
ADA Compliant	No
Bug Rating	B1-U2-G1
CA Prop 65	Lead
Dark Sky Rated	No
FCC Compliant	Yes
IP Rating	IP65
Location Rating	Wet
NSF Approved	No
ROHS Compliant	Yes
Safety Listing	cULus - Certified, cULus - Listed
California Ban	Lawful for sale
DLC Approved	No
Title 20	Exempt
T24/JA8 Compliant	No