Project / Job Name:

Location:

Fixture Type:

Notes:



**65-831R1** - 4 Foot; LED Tri-Proof Linear Fixture; CCT & Wattage Selectable; IP65 and IK08 Rated; 0-10V Dimming; 120V-347V; White / Gray Finish

## GENERAL

| | |
|---|---|
| Company | NUVO |
| EA Height | 4.33 |
| EA Width | 6.89 |
| EA Length | 49.61 |
| Bulb Included | Integrated |
| Material | Plastic |
| Fixture Type | Vapor Tight |
| Status | Active |
| Style | Utility |
| Surge Protection | Built-in surge protection - 2KV |
| Total Harmonic Distortion | 16.20% |
| CCT Selectable | Yes |
| Wattage Selectable | Yes |
| Finish Family | White |
| Amps | 0.333-0.115/0.417-0.144/0.500-0.173A |
| Has Camera | No |
| IOT Enabled | No |
| Lens Finish | Opaque |
| Lens Material | Polycarbonate (PC) |
| Power Factor | >0.96 |
| SDS Class | LED_Fixture |
| Indoor Outdoor | Indoor, Outdoor |
| Product Technology | LED |
| Incandescent Equivalent | 300W-400W |
| Serviceable Battery | No |
| Battery Indicator | No |
| Digital Display | No |

## ELECTRICAL

| | |
|---|---|
| CCT (Kelvin Temp) | 3000K/4000K/5000K |
| Dimmable | Yes-Dimmable |
| Hours Rated | 50000 |
| Beam Angle (degree) | 115 |
| Color Temp | Warm to Cool White |
| CRI | 80+ |
| Dimming Type | 0-10V Dimming |
| Operating Frequency | 50/60Hz |
| Operating Temp | -40F to +113F (-40C to +45C) |
| HID Equivalent | 125W-150W |
| Lumens | 5040L-7669L |
| Volts | 120V-347V |
| Watts | 40W/50W/60W |
| Max Lumens | 7669L |

## PHYSICAL

| | |
|---|---|
| Lamp Base | Integrated |
| Finish | White / Gray |
| ANSI Base | Integrated |
| Lamp Type | Integrated LED |
| Fixture Shape | Linear |
| Mounting Procedure | Ceiling/Wall |

## ADDITIONAL INFO

| | |
|---|---|
| Warranty | 5-Years |

## FEATURES

| | |
|---|---|
| Flicker Free | No |

## PACKAGING

| | |
|---|---|
| UPC | 045923651205 |
| Case Cube | 5.1391 |
| Case Height | 12.99 |
| Case Length | 49.61 |
| Case Quantity | 6 |
| Case UPC | 10045923651202 |
| Case Weight | 30.86 |
| Case Width | 13.78 |
| EA Cube | 0.8565 |
| EA Height | 4.33 |
| EA Length | 49.61 |
| EA Quantity | 1 |
| EA Weight | 5.14 |
| EA Width | 6.89 |
| Pack Type | Box |
| Web Height | 3.11 |
| Web Length | 47.24 |
| Web Width | 3.98 |

## COMPLIANCE

| | |
|---|---|
| CA Prop 65 | Lead |
| DLC ID | S-9ZKTYA; S-CAOZIN |
| FCC Compliant | Yes |
| IP Rating | IP65 |
| Location Rating | Wet |
| NSF Approved | Yes |
| ROHS Compliant | Yes |
| Safety Listing | cETLus - Listed |
| California Ban | Lawful for sale |
| DLC Approved | Yes |
| Title 20 | Exempt |
| T24/JA8 Compliant | No |



© Satco Products, Inc.
All rights reserved 2026