



Project / Job Name: \_\_\_\_\_

Location: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Notes: \_\_\_\_\_

**65-833R1** - 4 Foot; LED Tri-Proof Linear Fixture with Integrated Microwave Sensor; CCT & Wattage Selectable; IP65 and IK08 Rated; 120V-347V; White / Gray Finish



**GENERAL**

Company	NUVO
EA Height	3.15
EA Width	4.13
EA Length	49.21
Bulb Included	Integrated
Material	Plastic
Fixture Type	Vapor Tight
Status	Active
Style	Utility
Surge Protection	Built-in surge protection - 2KV
Total Harmonic Distortion	16.20%
CCT Selectable	Yes
Wattage Selectable	Yes
Finish Family	White
Amps	0.333-0.115/0.417-0.144/0.500-0.173A
Has Camera	No
Integrated Features	Integrated MW Sensor
IOT Enabled	No
Lens Finish	Opaque
Lens Material	Polycarbonate (PC)
Photo Cell	Integrated Microwave Sensor
Power Factor	>0.96
SDS Class	LED Fixture
Indoor Outdoor	Indoor, Outdoor
Product Technology	LED
Incandescent Equivalent	300W-400W

**ELECTRICAL**

CCT (Kelvin Temp)	3000K/4000K/5000K
Dimmable	Yes-Dimmable
Hours Rated	50000
Beam Angle (degree)	115
Color Temp	Warm to Cool White
CRI	80+
Dimming Type	0-10V, Bi-Level Dimmable, Integrated Sensor
Operating Frequency	50/60Hz
Operating Temp	-40F to +113F (-40C to +45C)
HID Equivalent	125W-150W
Lumens	5040L-7669L
Volts	120V-347V
Watts	40W/50W/60W

**PHYSICAL**

Lamp Base	Integrated
Finish	White / Gray
ANSI Base	Integrated
Lamp Type	Integrated LED
Fixture Shape	Linear

**ADDITIONAL INFO**

Warranty	5-Years
----------	---------

**FEATURES**

Flicker Free	No
--------------	----

**PACKAGING**

UPC	045923651304
Case Cube	5.1391
Case Height	12.99
Case Length	49.61
Case Quantity	6
Case UPC	10045923651301
Case Weight	32.19
Case Width	13.78
EA Cube	0.3705
EA Height	3.15
EA Length	49.21
EA Quantity	1
EA Weight	4.63
EA Width	4.13
Pack Type	Box
Web Height	3.11
Web Length	47.24
Web Width	3.98

**COMPLIANCE**

CA Prop 65	Lead
DLC ID	S-0F3SGU; S-RISVQ9
FCC Compliant	Yes
IP Rating	IP65
Location Rating	Wet
NSF Approved	Yes
ROHS Compliant	Yes
Safety Listing	cETLus - Listed
California Ban	Lawful for sale
DLC Approved	Yes
Title 20	Exempt
T24/JA8 Compliant	No