



Project / Job Name:

Location:

Fixture Type:

Notes:

65-902 - Bullet Outdoor SMART Security Camera;
Starfish enabled; Brown Finish



GENERAL

Company	NUVO
EA Height	9.69
EA Width	8.58
EA Length	8.04
Bulb Included	Integrated
Camera Resolution	1080P at 15fps; 1920x1080; 640x480 VGA
Starfish Communication Protocol	WiFi-2.4GHz; 802.11b/g/n; WPA/WPA2; WPA-PSK/WPA2-PSK
Camera DNR	3D Digital Noise Reduction
Dimmable Text	Only with Starfish App
Extends (in)	9.45
Material	Die-cast Aluminum
Fixture Type	Security Camera
Camera Focal Length	2.8
Camera Image Compression	H.264
Camera Image Sensor	1/2.9 Color CMOS
Status	Transitioning
Camera Storage Capacity	32GB SD Card Included; Optional 128GB Max SD Card
Style	Utility
Most Current Generation	65-902R1
Surge Protection	Built-in surge protection - 2KV
Camera Viewing Angle	150 D; 125 H; 85 V
Camera WDR	Digital Wide Dynamic
CCT Selectable	False
Wattage Selectable	False
Finish Family	Brown
Additional Info	For Non IOT Version See 65-712, 65-713, 65-718, 65-719
Amps	0.167-0.072A
Camera Audio	2-Way Communication
Camera Audio Compression	PCM
Has Camera	True
IOT Enabled	True
Lens Finish	Frost
Lens Material	Glass
Starfish Operational Humidity	20% to 85% non-condensing
Photo Cell	Has PIR Sensor
SDS Class	LED Fixture
Starfish Software Supported	AWS Cloud Security Servers, Tuya/Starfish App
Indoor/Outdoor	Outdoor
Product Technology	LED
Incandescent Equivalent	100W

ELECTRICAL

CCT (Kelvin Temp)	3000K
Dimmable	Yes-Dimmable
Hours Rated	50000
Beam Angle (degree)	50
Color Temp	Warm White
CRI	80+
Dimming Type	Smart-Starfish App only
Operating Frequency	60Hz
Operating Temp	-20C (-4F) to +60C (+140F)
Lumens	1900L
Volts	120V-277V
Watts	20W

PHYSICAL

Lamp Base	Integrated
Finish	Brown
ANSI Base	Integrated
Lamp Type	Integrated LED

ADDITIONAL INFO

Warranty	1-Year
Installation Notes	May be wired to recessed or external junction boxes.

FEATURES

Camera Night Vision	10 pcs; 850nm; LED; IR Distance 10m
---------------------	-------------------------------------