



Project / Job Name: \_\_\_\_\_

Location: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Notes: \_\_\_\_\_

**65-987** - LED Entryway Wall Pack; 10/15/20 Wattage Selectable; 30K/40K/50K CCT Selectable; White Finish



**GENERAL**

Company	NUVO
EA Height	5.0
EA Width	11.5
EA Length	7.5
Bulb Included	Integrated
Extends (in)	4.53
Material	Die-cast Aluminum
Fixture Type	Wall Pack
Product Notes	Photocell does not function in artificial light
Status	Active
Style	Utility
Surge Protection	Built-in surge protection - 2.5KV
Total Harmonic Distortion	<20%
CCT Selectable	Yes
Wattage Selectable	Yes
Finish Family	White
Amps	0.083-0.029/0.125-0.043/0.167-0.058A
Has Camera	No
Integrated Features	Integrated Photocell
IOT Enabled	No
Lens Finish	Prismatic
Lens Material	Polycarbonate (PC)
Photo Cell	Has Photocell
Power Factor	>0.9
SDS Class	LED_Fixture
Indoor Outdoor	Outdoor
Product Technology	LED
Fluor Equiv	42W
Incandescent Equivalent	150W

**PACKAGING**

UPC	045923404108
Case Cube	1.1899
Case Height	10.87
Case Length	12.01
Case Quantity	4
Case UPC	10045923404105
Case Weight	13.67
Case Width	15.75
EA Cube	0.2496
EA Height	5.0
EA Length	7.5
EA Quantity	1
EA Weight	3.09
EA Width	11.5
Pack Type	Box
Web Height	10.96
Web Width	6.86

**COMPLIANCE**

ADA Compliant	No
Bug Rating	B1-U3-G1
CA Prop 65	Lead
DLC ID	S-MGDDN0
FCC Compliant	Yes
IP Rating	IP65
Location Rating	Wet
ROHS Compliant	Yes
Safety Listing	cULus
California Ban	Lawful for sale
DLC Approved	Yes
Title 20	Exempt
T24/JA8 Compliant	No

**ELECTRICAL**

CCT (Kelvin Temp)	3000K/4000K/5000K
Dimmable	Yes-Dimmable
Hours Rated	50000
Beam Angle (degree)	100
Color Temp	Soft White to Natural Light
CRI	80+
Dimming Type	0-10V Dimming
Operating Frequency	50/60Hz
Operating Temp	-40F to +122F (-40C to +50C)
HID Equivalent	100W
Lumens	1410L-2839L
Volts	120V-347V
Watts	10W/15W/20W

**PHYSICAL**

Lamp Base	Integrated
Finish	WHITE
ANSI Base	Integrated
Lamp Type	Integrated LED

**ADDITIONAL INFO**

Warranty	5-Years
----------	---------

**FEATURES**

Flicker Free	No
--------------	----