



Project / Job Name: \_\_\_\_\_

Location: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Notes: \_\_\_\_\_

**67-101** - Red LED Exit Sign, 90min Ni-Cad backup, 120/277V, Single/Dual Face, Universal Mounting; White Finish



**GENERAL**

Company	NUVO
EA Height	7.48
EA Width	2.36
EA Length	12.05
Bulb Included	Integrated
Material	Thermoplastic
Fixture Type	Exit Sign
Includes	Mounting hardware and accessories
Product Notes	UL94V-0, Thermoplastic, 2.4V AA300mAh Ni-Cad Battery, 90 minutes duration, 24 hour charge time, 10C-40C; Letter Height: 6 in.; Letter Stroke: 0.75 in.
Status	Active
Style	Utility
Surge Protection	Built-in surge protection - 3KV
CCT Selectable	No
Wattage Selectable	No
Finish Family	White
Additional Info	Input Wattage: 2.5W; Output Wattage: 0.4W; Energy Used in Maintenance Mode: 2.5W
Amps	0.008/0.003A
Has Camera	No
IOT Enabled	No
SDS Class	LED_Fixture
Sloped Ceiling Compatible	No
Indoor Outdoor	Indoor
Product Technology	LED

**ELECTRICAL**

Dimmable	Non-Dimmable
Operating Frequency	60Hz
Operating Temp	+50F to +104F (+10C to +40C)
Volts	120V/277V
Watts	2.5W

**PHYSICAL**

Lamp Base	Integrated
Finish	WHITE
ANSI Base	Integrated
Lamp Type	Integrated LED

**ADDITIONAL INFO**

Warranty	2-Years
----------	---------

**PACKAGING**

UPC	045923675683
Case Cube	1.7502
Case Height	15.75
Case Length	12.6
Case Quantity	12
Case UPC	10045923675680
Case Weight	30.36
Case Width	15.24
EA Cube	0.1231
EA Height	7.48
EA Length	12.05
EA Quantity	1
EA Weight	2.48
EA Width	2.36
Pack Type	Box
Web Height	7.25
Web Length	1.81
Web Width	11.81

**COMPLIANCE**

CA Prop 65	Lead
FCC Compliant	Yes
Location Rating	Damp
ROHS Compliant	Yes
Safety Listing	ULus - Certified, ULus - Listed
California Ban	Lawful for sale
DLC Approved	No
Title 20	Yes
T24/JA8 Compliant	No