



Project / Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

67-102 - Red LED Exit Sign, 90min Ni-Cad backup, 120V/277V, Single/Dual Face, Universal Mounting, Steel/NYC; White Finish



GENERAL

Company	NUVO
EA Height	2.56
EA Width	10.04
EA Length	15.79
Bulb Included	Integrated
Material	Steel
Fixture Type	Exit Sign
Includes	Mounting hardware and accessories
Product Notes	20-gauge Steel, 3.6V AA300mAh Ni-Cad Battery, 90 minutes duration, 24 hour charge time, 10C-40C; Letter Height: 8 in.; Letter Stroke: 1 in.
Status	Active
Style	Utility
Surge Protection	Built-in surge protection - 3KV
CCT Selectable	No
Wattage Selectable	No
Finish Family	White
Additional Info	Input Wattage: 2.0W; Output Wattage: 0.4W; Energy Used in Maintenance Mode: 2.0W
Amps	0.017/0.007A
Has Camera	No
IOT Enabled	No
SDS Class	LED_Fixture
Sloped Ceiling Compatible	No
Indoor Outdoor	Indoor
Product Technology	LED

ELECTRICAL

Dimmable	Non-Dimmable
Operating Frequency	50/60Hz
Operating Temp	+50F to +104F (+10C to +40C)
Volts	120V/277V
Watts	2W

PHYSICAL

Lamp Base	Integrated
Finish	WHITE
ANSI Base	Integrated
Lamp Type	Integrated LED

ADDITIONAL INFO

Warranty	2-Years
----------	---------

PACKAGING

UPC	045923675690
Case Cube	1.1416
Case Height	11.22
Case Length	16.54
Case Quantity	4
Case UPC	10045923675697
Case Weight	29.13
Case Width	10.63
EA Cube	0.2349
EA Height	2.56
EA Length	15.79
EA Quantity	1
EA Weight	7.14
EA Width	10.04
Pack Type	Box
Web Height	9.63
Web Length	2.31
Web Width	14.56

COMPLIANCE

CA Prop 65	Lead
FCC Compliant	No
Location Rating	Damp
ROHS Compliant	Yes
Safety Listing	ULus - Certified, ULus - Listed
California Ban	Lawful for sale
DLC Approved	No
Title 20	Yes
T24/JA8 Compliant	No