



Project / Job Name: \_\_\_\_\_

Location: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Notes: \_\_\_\_\_

**67-124** - Combination Red Exit Sign/Emergency Light, 90min Ni-Cad backup, 120/277V, Tri Head, Single/Dual Face, Universal Mounting, Steel/NYC; White Finish



GENERAL	
Company	NUVO
EA Height	2.76
EA Width	15.16
EA Length	15.79
Bulb Included	Integrated
Material	Steel
Fixture Type	Exit Sign
Includes	Mounting hardware and accessories
Product Notes	20-gauge Steel, 3.6V AA800mAh Ni-Cad Battery, 90 minutes duration, 24 hour charge time, 10C-40C; Letter Height: 8 in.; Letter Stroke: 1 in.; Path of Egress: 6 Ft.
Status	Active
Style	Utility
Surge Protection	Built-in surge protection - 3KV
CCT Selectable	No
Wattage Selectable	No
Finish Family	White
Additional Info	Input Wattage: 3.0W; Output Wattage: 1.6W; Energy Used in Maintenance Mode: 3.0W
Amps	0.025/0.108A
Has Camera	No
IOT Enabled	No
Lens Finish	Clear
Lens Material	Polycarbonate (PC)
SDS Class	LED_Fixture
Sloped Ceiling Compatible	No
Indoor Outdoor	Indoor
Product Technology	LED
Fixture Lamp Count	3
Incandescent Equivalent	25W

ELECTRICAL	
CCT (Kelvin Temp)	5700K
Dimmable	Non-Dimmable
CRI	70+
Operating Frequency	50/60Hz
Operating Temp	+50F to +104F (+10C to +40C)
Lumens	330L
Volts	120V/277V
Watts	3W

PHYSICAL	
Lamp Base	Integrated
Finish	WHITE
ANSI Base	Integrated
Lamp Type	Integrated LED

ADDITIONAL INFO	
Warranty	2-Years

PACKAGING	
UPC	045923675782
Case Cube	1.8106
Case Height	12.01
Case Length	15.75
Case Quantity	4
Case UPC	10045923675789
Case Weight	29.13
Case Width	16.54
EA Cube	0.3823
EA Height	2.76
EA Length	15.79
EA Quantity	1
EA Weight	7.14
EA Width	15.16
Pack Type	Box
Web Height	14.88
Web Length	2.31
Web Width	14.56

COMPLIANCE	
CA Prop 65	Lead
FCC Compliant	No
Location Rating	Damp
ROHS Compliant	Yes
Safety Listing	ULus - Certified, ULus - Listed
California Ban	Lawful for sale
DLC Approved	No
Title 20	Yes
T24 Compliant	No