Project / Job Name:

Location:

Fixture Type:

Notes:



67-130 - Emergency Light, 90min Ni-Cad backup, 120/277V, Dual Head, Universal Mounting; White Finish

GENERAL

Company	NUVO
EA Height	3.11
EA Width	4.69
EA Length	13.54
Bulb Included	Integrated
Material	Thermo Plastic
Fixture Type	Emergency Light
Includes	Mounting hardware and accessories
Product Notes	UL94V-0, Thermoplastic, 3.6V AA1000mAh Ni-Cad Battery, 90 minutes duration, 24 hour charge time, 10C-40C; Path of Egress: 6 Ft.
Status	Active
Style	Utility
Surge Protection	Built-in surge protection - 3KV
CCT Selectable	No
Wattage Selectable	No
Finish Family	White
Additional Info	Input Wattage: 0.8W; Output Wattage: 2W; Energy Used in Maintenance Mode: 0.8W
Amps	0.007/0.003A
Has Camera	No
IOT Enabled	No
Lens Finish	Clear
Lens Material	Polycarbonate (PC)
SDS Class	LED_Fixture
Sloped Ceiling Compatible	No
Indoor Outdoor	Indoor
Product Technology	LED
Fixture Lamp Count	2
Incandescent Equivalent	6W
Serviceable Battery	No
Battery Indicator	No
Digital Display	No

ELECTRICAL

CCT (Kelvin Temp)	5700K
Dimmable	Non-Dimmable
CRI	70+
Operating Frequency	50/60Hz
Operating Temp	+50F to +104F (+10C to +40C)
Lumens	210L
Volts	120V/277V
Watts	0.8W
Battery Chemistry	Ni-Cad
Replaceable Battery Type	AA

PHYSICAL

Lamp Base	Integrated
Finish	WHITE
ANSI Base	Integrated
Lamp Type	Integrated LED
Mounting Procedure	Ceiling/Wall

ADDITIONAL INFO

Warranty	2-Years

PACKAGING

UPC	045923675799
Case Cube	1.5548
Case Height	13.19
Case Length	13.98
Case Quantity	12
Case UPC	10045923675796
Case Weight	14.08
Case Width	14.57
EA Cube	0.1143
EA Height	3.11
EA Length	13.54
EA Quantity	1
EA Weight	1.15
EA Width	4.69
Pack Type	Box
Web Height	4.5
Web Length	2.88
Web Width	12.5

COMPLIANCE

CA Prop 65	Lead
FCC Compliant	Yes
Location Rating	Damp
ROHS Compliant	Yes
Safety Listing	cULus - Certified, cULus - Listed
California Ban	Lawful for sale
UL Application	Unit equipment
DLC Approved	No
Title 20	Yes
T24/JA8 Compliant	No

© Satco Products, Inc.
All rights reserved 2026