



Project / Job Name: \_\_\_\_\_

Location: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Notes: \_\_\_\_\_

**67-131** - Emergency Light, 90min Ni-Cad backup, 120/277V, Dual Head, Universal Mounting, Remote Compatible; White Finish



**GENERAL**

Company	NUVO
EA Height	3.11
EA Width	4.69
EA Length	13.54
Bulb Included	Integrated
Material	Thermoplastic
Fixture Type	Emergency Light
Includes	Mounting hardware and accessories
Product Notes	UL94V-0, Thermoplastic, 3.6V AA1000mAh Ni-Cad Battery, 90 minutes duration, 24 hour charge time, 10C-40C, Remote Compatible; Path of Egress: 6 Ft.
Status	Active
Style	Utility
Surge Protection	Built-in surge protection - 3KV
CCT Selectable	No
Wattage Selectable	No
Finish Family	White
Additional Info	Input Wattage: 1W; Output Wattage: 2W; Energy Used in Maintenance Mode: 0.8W
Amps	0.008/0.004A
Has Camera	No
IOT Enabled	No
Lens Finish	Clear
Lens Material	Polycarbonate (PC)
SDS Class	LED_Fixture
Sloped Ceiling Compatible	No
Indoor Outdoor	Indoor
Product Technology	LED
Fixture Lamp Count	2
Incandescent Equivalent	15W

**PACKAGING**

UPC	045923675805
Case Cube	1.5548
Case Height	13.19
Case Length	13.98
Case Quantity	12
Case UPC	10045923675802
Case Weight	15.79
Case Width	14.57
EA Cube	0.1143
EA Height	3.11
EA Length	13.54
EA Quantity	1
EA Weight	1.29
EA Width	4.69
Pack Type	Box
Web Height	4.5
Web Length	2.88
Web Width	12.5

**COMPLIANCE**

CA Prop 65	Lead
FCC Compliant	Yes
Location Rating	Damp
ROHS Compliant	Yes
Safety Listing	cULus - Certified, cULus - Listed
California Ban	Lawful for sale
UL Application	Unit equipment
DLC Approved	No
Title 20	Yes
T24/JA8 Compliant	No

**ELECTRICAL**

CCT (Kelvin Temp)	5700K
Dimmable	Non-Dimmable
CRI	70+
Operating Frequency	50/60Hz
Operating Temp	+50F to +104F (+10C to +40C)
Lumens	210L
Volts	120V/277V
Watts	1W

**PHYSICAL**

Lamp Base	Integrated
Finish	WHITE
ANSI Base	Integrated
Lamp Type	Integrated LED

**ADDITIONAL INFO**

Warranty	2-Years
----------	---------