



Project / Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

67-132 - Emergency Light, 90min Ni-Cad backup, 120-277V, Dual Head, Universal Mounting, Steel/NYC; White Finish



GENERAL

Company	NUVO
EA Height	2.68
EA Width	10.24
EA Length	13.43
Bulb Included	Integrated
Material	Steel
Fixture Type	Emergency Light
Includes	Mounting hardware and accessories
Product Notes	20-gauge Steel, 3.6V AA1000mAh Ni-Cad Battery, 90 minutes duration, 24 hour charge time, 10C-40C; Path of Egress: 6 Ft.
Status	Active
Style	Utility
Surge Protection	Built-in surge protection - 3KV
CCT Selectable	No
Wattage Selectable	No
Finish Family	White
Additional Info	Input Wattage: 1.5W; Output Wattage: 2W; Energy Used in Maintenance Mode: 2.5W
Amps	0.013/0.005A
Has Camera	No
IOT Enabled	No
Lens Finish	Clear
Lens Material	Thermo Plastic (PBT)
SDS Class	LED_Fixture
Sloped Ceiling Compatible	No
Indoor Outdoor	Indoor
Product Technology	LED
Fixture Lamp Count	2
Incandescent Equivalent	15W

PACKAGING

UPC	045923675812
Case Cube	1.0488
Case Height	11.81
Case Length	10.83
Case Quantity	4
Case UPC	10045923675819
Case Weight	11.18
Case Width	14.17
EA Cube	0.2133
EA Height	2.68
EA Length	13.43
EA Quantity	1
EA Weight	2.74
EA Width	10.24
Pack Type	Box
Web Height	9.88
Web Length	2.0
Web Width	12.0

COMPLIANCE

CA Prop 65	Lead
FCC Compliant	No
Location Rating	Damp
ROHS Compliant	Yes
Safety Listing	ULus - Certified, ULus - Listed
California Ban	Lawful for sale
DLC Approved	No
Title 20	Yes
T24/JA8 Compliant	No

ELECTRICAL

CCT (Kelvin Temp)	5700K
Dimmable	Non-Dimmable
CRI	70+
Operating Frequency	50/60Hz
Operating Temp	+50F to +104F (+10C to +40C)
Lumens	220L
Volts	120V/277V
Watts	1.5W

PHYSICAL

Lamp Base	Integrated
Finish	WHITE
ANSI Base	Integrated
Lamp Type	Integrated LED

ADDITIONAL INFO

Warranty	2-Years
----------	---------