Project / Job Name:

Location:

Fixture Type:

Notes:



**67-136** - Remote Emergency Light, Low-Voltage Backup, Single Head, White Finish, Wet Location Rated

## GENERAL

| | |
|---|---|
| Company | NUVO |
| EA Height | 6.5 |
| EA Width | 4.72 |
| EA Length | 4.72 |
| Bulb Included | Integrated |
| Diameter | 4.5 |
| Material | Thermo Plastic |
| Fixture Type | Emergency Light |
| Includes | Mounting hardware and accessories |
| Product Notes | UL94V-0, Thermoplastic, -25C-50C |
| Status | Active |
| Style | Utility |
| Surge Protection | Built-in surge protection - 3KV |
| CCT Selectable | No |
| Wattage Selectable | No |
| Finish Family | White |
| Additional Info | Input Wattage: 1W; Output Wattage: 1W; 90 Minute Battery Run Time |
| Amps | 0.004/0.002A |
| Has Camera | No |
| IOT Enabled | No |
| Lens Finish | Clear |
| Lens Material | Polycarbonate (PC) |
| SDS Class | LED_Fixture |
| Sloped Ceiling Compatible | No |
| Indoor Outdoor | Indoor, Outdoor |
| Product Technology | LED |
| Fixture Lamp Count | 1 |
| Incandescent Equivalent | 15W |
| Battery Discharge Time Minutes | 90 |
| Serviceable Battery | No |
| Battery Indicator | No |
| Digital Display | No |

## ELECTRICAL

| | |
|---|---|
| CCT (Kelvin Temp) | 6000K |
| Dimmable | Non-Dimmable |
| CRI | 70+ |
| Operating Frequency | 60Hz |
| Operating Temp | -13F to +122F (-25C to +50C) |
| Lumens | 100L |
| Volts | 3.6V/12V |
| Watts | 1W |

## PHYSICAL

| | |
|---|---|
| Lamp Base | Integrated |
| Finish | WHITE |
| ANSI Base | Integrated |
| Lamp Type | Integrated LED |
| Mounting Procedure | Ceiling/Wall |

## ADDITIONAL INFO

| | |
|---|---|
| Warranty | 2-Years |

## PACKAGING

| | |
|---|---|
| UPC | 045923675850 |
| Case Cube | 1.2216 |
| Case Height | 10.24 |
| Case Length | 13.78 |
| Case Quantity | 12 |
| Case UPC | 10045923675857 |
| Case Weight | 6.85 |
| Case Width | 14.96 |
| EA Cube | 0.0838 |
| EA Height | 6.5 |
| EA Length | 4.72 |
| EA Quantity | 1 |
| EA Weight | 0.56 |
| EA Width | 4.72 |
| Pack Type | Box |
| Web Length | 6.06 |
| Web Width | 4.5 |

## COMPLIANCE

| | |
|---|---|
| CA Prop 65 | Lead |
| FCC Compliant | No |
| Location Rating | Wet |
| ROHS Compliant | Yes |
| Safety Listing | cULus - Certified, cULus - Listed |
| California Ban | Lawful for sale |
| UL Application | REMOTE LAMP ASSEMBLIES |
| DLC Approved | No |
| Title 20 | Exempt |
| T24/JA8 Compliant | No |



© Satco Products, Inc.
All rights reserved 2026