



Project / Job Name: \_\_\_\_\_

Location: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Notes: \_\_\_\_\_

**67-530** - Running Man Green Edge Lit Exit Sign; 120-347V; 2HR backup; Single/Dual Face; Universal Surface or Recessed Mounting; Pivoting Panel; Brushed Aluminum Finish



### GENERAL

Company	SATCO
EA Height	8.66
EA Width	4.72
EA Length	18.5
Bulb Included	Integrated
Material	Aluminum
Fixture Type	Exit Sign
Product Notes	Ni-Cad Battery; 120 minute discharge time
Status	Active
Style	Utility
Surge Protection	Built-in surge protection - 6KV
Total Harmonic Distortion	120%-140%
CCT Selectable	No
Wattage Selectable	No
Finish Family	Metallic
Amps	0.028-0.009A
Has Camera	No
IOT Enabled	No
Lens Finish	Clear
Lens Material	Acrylic
Power Factor	0.38
SDS Class	LED_Fixture
Sloped Ceiling Compatible	No
Indoor Outdoor	Indoor
Product Technology	LED

### ELECTRICAL

CCT (Kelvin Temp)	5700K
Dimmable	Non-Dimmable
CRI	80+
Operating Frequency	60Hz
Operating Temp	+50F to +104F (+10C to +40C)
Volts	120V-347V
Watts	3W

### PHYSICAL

Lamp Base	Integrated
Finish	Brushed Aluminum
ANSI Base	Integrated
Lamp Type	Integrated LED

### ADDITIONAL INFO

Warranty	2-Years
----------	---------

### PACKAGING

UPC	045923675867
Case Cube	1.5338
Case Height	9.25
Case Length	18.9
Case Quantity	3
Case UPC	10045923675864
Case Weight	22.49
Case Width	15.16
EA Cube	0.4376
EA Height	8.66
EA Length	18.5
EA Quantity	1
EA Weight	6.39
EA Width	4.72
Pack Type	Box

### COMPLIANCE

CA Prop 65	Lead
IP Rating	IP40
Location Rating	Damp
ROHS Compliant	Yes
Safety Listing	CSAus
California Ban	Non-Compliant
Title 20	No
T24 Compliant	No