



Project / Job Name:

Location:

Fixture Type:

Notes:

**67-583** - Emergency Light; 120-347V; 2HR Backup; Universal Mounting; Wet Location; Low Temperature; Remote Compatible



#### GENERAL

Company	SATCO
EA Height	10.43
EA Width	2.83
EA Length	12.48
Bulb Included	Integrated
Material	Thermoplastic
Fixture Type	Emergency Light
Product Notes	Ni-Cad Battery; 120 minute discharge time; Remote Compatible; 24 Hour Recharge Time
Status	Active
Style	Utility
Surge Protection	Built-in surge protection - 6KV
Total Harmonic Distortion	120%-140%
CCT Selectable	False
Wattage Selectable	False
Finish Family	White
Additional Info	Remote Capable Power Rating: 6V/3W; Low Temperature Model
Amps	0.029-0.010A
Has Camera	False
IOT Enabled	False
Lens Finish	Clear
Lens Material	Polycarbonate (PC)
Power Factor	0.45
SDS Class	LED_Fixture
Sloped Ceiling Compatible	No
Indoor/Outdoor	Indoor and Outdoor
Product Technology	LED

#### ELECTRICAL

CCT (Kelvin Temp)	5000K
Dimmable	Non-Dimmable
Color Temp	Natural Light
CRI	80+
Operating Frequency	50/60Hz
Operating Temp	-25C (-13F) to +50C (+122F)
Lumens	300L
Volts	120V-347V
Watts	3.5W

#### PHYSICAL

Lamp Base	Integrated
Finish	WHITE
ANSI Base	Integrated
Lamp Type	Integrated LED

#### ADDITIONAL INFO

Warranty	2-Years
----------	---------

#### PACKAGING

UPC	045923676000
Case Cube	1.4971
Case Height	13.19
Case Length	18.11
Case Quantity	6
Case UPC	10045923676007
Case Weight	19.62
Case Width	10.83
EA Cube	0.2132
EA Height	10.43
EA Length	12.48
EA Quantity	1
EA Weight	2.65
EA Width	2.83
Inner Cube	0.0
Pack Type	Box

#### COMPLIANCE

CA Regulations	Non-Compliant - Never Tested
CA Prop 65	Lead
CA Status	Non-Compliant
FCC Compliant	True
IP Rating	IP65
Location Rating	Wet
ROHS Compliant	Yes
Safety Listing	CSAus
CA Compliance Text	Non-Compliant
Title 20	No
T24 Compliant	False