



**68-102 - DOMINO; 50 Watt LED Backlit Flat Panel; 2 ft. x 4 ft.; CCT Selectable; 120-347 Volt**


**GENERAL**

Company	NUVO
EA Height	24.45
EA Width	2.32
EA Length	48.23
Bulb Included	Integrated
Starfish Communication Protocol	Domino Bluetooth Mesh 2.4 GHz
Material	Steel
Fixture Type	Flat Panel
Status	Active
Surge Protection	Built-in surge protection - 2KV
CCT Selectable	Yes
Wattage Selectable	No
Finish Family	White
Amps	0.417-0.144A
Has Camera	No
Integrated Features	Integrated NLC Sensor
IOT Enabled	Yes
Lens Finish	White
Lens Material	Polystyrene (PS)
Lensed	Yes
Photo Cell	No
Power Factor	0.9
Sloped Ceiling Compatible	No
Indoor Outdoor	Indoor
Product Technology	LED
Incandescent Equivalent	250W

**ELECTRICAL**

CCT (Kelvin Temp)	3000K-5000K
Dimmable	Yes-Dimmable
Hours Rated	50000
Beam Angle (degree)	120
Color Temp	Soft White to Natural Light
CRI	80+
Dimming Type	Only With Domino App
Operating Frequency	50/60Hz
Operating Temp	-4F to +113F (-20C to +45C)
Lumens	6250L
Volts	120V-347V
Watts	50W

**PHYSICAL**

Lamp Base	Integrated
Finish	WHITE
ANSI Base	Integrated
Lamp Type	Integrated LED

**ADDITIONAL INFO**

Warranty	5-Years
----------	---------

**PACKAGING**

UPC	045923683459
Case Cube	1.5832
Case Height	24.45
Case Length	48.23
Case Quantity	1
Case UPC	10045923683456
Case Weight	12.24
Case Width	2.32
EA Cube	1.5832
EA Height	24.45
EA Length	48.23
EA Quantity	1
EA Weight	12.24
EA Width	2.32
Pack Type	Box
Web Height	1.86
Web Length	47.76
Web Width	23.74

**COMPLIANCE**

ADA Compliant	No
CA Prop 65	Lead
DLC ID	S-C11RZR; S-G6MNVR
FCC Compliant	Yes
IP Rating	IP20
Location Rating	Damp
NSF Approved	Yes
ROHS Compliant	Yes
Safety Listing	cETLus
California Ban	Lawful for sale
DLC Approved	Yes
Title 20	Exempt
T24/JA8 Compliant	No