



68-116 - DOMINO; 50 Watt LED 2 ft. x 4 ft. Troffer; Emergency Battery; Integrated Sensor; CCT Selectable; 120-347 Volt


GENERAL

Company	NUVO
EA Height	24.45
EA Width	2.32
EA Length	48.23
Bulb Included	Integrated
Starfish Communication Protocol	Domino Bluetooth Mesh 2.4 GHz
Dimmable Text	Only With Domino App
Material	Steel
Fixture Type	Troffer
Status	Active
Surge Protection	Built-in surge protection - 2KV
CCT Selectable	Yes
Wattage Selectable	No
Finish Family	White
Amps	0.417-0.144A
Has Camera	No
IOT Enabled	Yes
Lens Finish	White
Lens Material	Polystyrene (PS)
Lensed	Yes
Photo Cell	No
Power Factor	0.9
Sloped Ceiling Compatible	No
Indoor Outdoor	Indoor
Product Technology	LED
Incandescent Equivalent	250W

ELECTRICAL

CCT (Kelvin Temp)	3000K-5000K
Dimmable	Yes-Dimmable
Hours Rated	50000
Beam Angle (degree)	120
Color Temp	RGB and Tunable White
CRI	80
Dimming Type	Only With Domino App
Operating Frequency	50/60Hz
Operating Temp	-20C (-4F) to +45C (+113F)
Lumens	6250L
Volts	120V-347V
Watts	50W

PHYSICAL

Lamp Base	Integrated
Finish	WHITE
ANSI Base	Integrated
Lamp Type	Integrated LED

ADDITIONAL INFO

Warranty	5-Years
----------	---------

PACKAGING

UPC	045923683619
Case Cube	1.5832
Case Height	24.45
Case Length	48.23
Case Quantity	1
Case UPC	10045923683616
Case Weight	16.1
Case Width	2.32
EA Cube	1.5832
EA Height	24.45
EA Length	48.23
EA Quantity	1
EA Weight	16.1
EA Width	2.32
Pack Type	Box
Web Height	1.91
Web Length	47.76
Web Width	23.74

COMPLIANCE

ADA Compliant	No
CA Prop 65	Lead
DLC ID	S-4QBLPL; S-MQ75LJ
FCC Compliant	Yes
IP Rating	IP20
Location Rating	Damp
NSF Approved	No
ROHS Compliant	Yes
Safety Listing	cULus
California Ban	Lawful for sale
DLC Approved	Yes
Title 20	Yes
T24 Compliant	No