Project / Job Name:

Location:

Fixture Type:

Notes:



68-126 - DOMINO; 50 Watt LED 4 ft. Linear Strip Light; Integrated Sensor; Emergency Battery; Tunable White Max 5000K; 120-347 Volt

GENERAL

Company	NUVO
EA Height	3.94
EA Width	3.39
EA Length	48.62
Bulb Included	Integrated
Starfish Communication Protocol	Domino Bluetooth Mesh 2.4 GHz
Material	Steel
Fixture Type	Strip Light
Status	Active
Surge Protection	Built-in surge protection - 2KV
CCT Selectable	Yes
Wattage Selectable	No
Finish Family	White
Amps	0.417-0.144A
Has Camera	No
Integrated Features	Integrated NLC Sensor
IOT Enabled	Yes
Lens Finish	White
Lens Material	Polycarbonate (PC)
Lensed	Yes
Photo Cell	No
Power Factor	0.9
Sloped Ceiling Compatible	Yes
Indoor Outdoor	Indoor
Product Technology	LED
Incandescent Equivalent	125W
Serviceable Battery	No
Battery Indicator	No
Digital Display	No

ELECTRICAL

CCT (Kelvin Temp)	3500K-5000K
Dimmable	Yes-Dimmable
Hours Rated	50000
Beam Angle (degree)	110
Color Temp	Tunable White
CRI	80+
Dimming Type	Only With Domino App
Operating Frequency	50/60Hz
Operating Temp	-4F to +113F (-20C to +45C)
Lumens	6500L
Volts	120V-347V
Watts	50W
Connection	Hardwire
Battery Chemistry	LiFePO4

PHYSICAL

Lamp Base	Integrated
Finish	WHITE
ANSI Base	Integrated
Lamp Type	Integrated LED
Fixture Shape	Linear
Mounting Procedure	Ceiling/Wall

ADDITIONAL INFO

Warranty	5-Years

PACKAGING

UPC	045923683565
Case Cube	2.8226
Case Height	9.06
Case Length	49.21
Case Quantity	6
Case UPC	10045923683562
Case Weight	35.9
Case Width	10.94
EA Cube	0.3758
EA Height	3.94
EA Length	48.62
EA Quantity	1
EA Weight	5.54
EA Width	3.39
Pack Type	Box
Web Height	3.2
Web Length	47.99
Web Width	2.68

COMPLIANCE

ADA Compliant	No
Bug Rating	B2-U3-G2
CA Prop 65	Lead
DLC ID	S-837PMN; S-SKB3Z1; S-17YKQD
FCC Compliant	Yes
IP Rating	IP20
Location Rating	Damp
NSF Approved	No
ROHS Compliant	Yes
Safety Listing	cULus
California Ban	Lawful for sale
DLC Approved	Yes
Title 20	Yes
T24/JA8 Compliant	No

© Satco Products, Inc.
All rights reserved 2026