



Project / Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

68-161 - DOMINO; 45 Watt LED Wide Beam Angle Canopy Light; White Finish; 120-347 Volt



GENERAL

| | |
|---------------------------------|---------------------------------|
| Company | NUVO |
| EA Height | 13.98 |
| EA Width | 4.53 |
| EA Length | 11.34 |
| Bulb Included | Integrated |
| Starfish Communication Protocol | Domino Bluetooth Mesh 2.4 GHz |
| Material | Die-cast Aluminum |
| Fixture Type | Canopy |
| Status | Active |
| Surge Protection | Built-in surge protection - 4KV |
| CCT Selectable | Yes |
| Wattage Selectable | No |
| Finish Family | White |
| Amps | 0.375-0.130A |
| Has Camera | No |
| Integrated Features | Integrated NLC Sensor |
| IOT Enabled | Yes |
| Lens Finish | Clear |
| Lens Material | Polycarbonate (PC) |
| Lensed | Yes |
| Photo Cell | No |
| Power Factor | 0.9 |
| Sloped Ceiling Compatible | Yes |
| Indoor Outdoor | Indoor and Outdoor |
| Product Technology | LED |
| Incandescent Equivalent | 125W |

ELECTRICAL

| | |
|---------------------|------------------------------|
| CCT (Kelvin Temp) | 3000K/4000K/5000K |
| Dimmable | Yes-Dimmable |
| Hours Rated | 50000 |
| Beam Angle (degree) | 190 |
| Color Temp | Soft White to Natural Light |
| CRI | 80+ |
| Dimming Type | Only With Domino App |
| Operating Frequency | 50/60Hz |
| Operating Temp | -22F to +122F (-30C to +50C) |
| Lumens | 6143L/6778L/6677L |
| Volts | 120V-347V |
| Watts | 45W |

PHYSICAL

| | |
|---------------|----------------|
| Lamp Base | Integrated |
| Finish | WHITE |
| ANSI Base | Integrated |
| Lamp Type | Integrated LED |
| Fixture Shape | Square |

ADDITIONAL INFO

| | |
|----------|---------|
| Warranty | 5-Years |
|----------|---------|

PACKAGING

| | |
|---------------|----------------|
| UPC | 045923683404 |
| Case Cube | 1.933 |
| Case Height | 12.13 |
| Case Length | 18.9 |
| Case Quantity | 4 |
| Case UPC | 10045923683401 |
| Case Weight | 21.12 |
| Case Width | 14.57 |
| EA Cube | 0.4156 |
| EA Height | 13.98 |
| EA Length | 11.34 |
| EA Quantity | 1 |
| EA Weight | 4.84 |
| EA Width | 4.53 |
| Pack Type | Box |
| Web Height | 4.88 |
| Web Length | 9.56 |
| Web Width | 9.56 |

COMPLIANCE

| | |
|-------------------|-----------------|
| ADA Compliant | No |
| Bug Rating | B2-U3-G3 |
| CA Prop 65 | Lead |
| DLC ID | S-2G6G9R |
| FCC Compliant | Yes |
| IP Rating | IP65 |
| Location Rating | Wet |
| NSF Approved | No |
| ROHS Compliant | Yes |
| Safety Listing | cULus |
| California Ban | Lawful for sale |
| DLC Approved | Yes |
| Title 20 | Exempt |
| T24/JA8 Compliant | No |