Project / Job Name:

Location:

Fixture Type:

Notes:



68-163 - DOMINO; 45 Watt LED Wide Beam Angle Canopy Light; Bronze Finish; 120-347 Volt

WET LOCATION · DIMMABLE · FC · RoHS COMPLIANT · CCT SELECTABLE · 50,000 HOURS · 5 YEAR WARRANTY · IP 65

GENERAL

Company	NUVO
EA Height	13.98
EA Width	4.53
EA Length	11.34
Bulb Included	Integrated
Starfish Communication Protocol	Domino Bluetooth Mesh 2.4 GHz
Material	Die-cast Aluminum
Fixture Type	Canopy
Status	Active
Surge Protection	Built-in surge protection - 4KV
CCT Selectable	Yes
Wattage Selectable	No
Finish Family	Bronze
Amps	0.375-0.130A
Has Camera	No
Integrated Features	Integrated NLC Sensor
IOT Enabled	Yes
Lens Finish	Clear
Lens Material	Polycarbonate (PC)
Lensed	Yes
Photo Cell	No
Power Factor	0.9
Sloped Ceiling Compatible	Yes
Indoor Outdoor	Indoor and Outdoor
Product Technology	LED
Incandescent Equivalent	125W
Serviceable Battery	No
Battery Indicator	No
Digital Display	No

ELECTRICAL

CCT (Kelvin Temp)	3000K/4000K/5000K
Dimmable	Yes-Dimmable
Hours Rated	50000
Beam Angle (degree)	190
Color Temp	Soft White to Natural Light
CRI	80+
Dimming Type	Only With Domino App
Operating Frequency	50/60Hz
Operating Temp	-22F to +122F (-30C to +50C)
Lumens	6143L/6778L/6677L
Volts	120V-347V
Watts	45W
Max Lumens	6778L
Connection	Hardwire

PHYSICAL

Lamp Base	Integrated
Finish	BRONZE
ANSI Base	Integrated
Lamp Type	Integrated LED
Fixture Shape	Square
Mounting Procedure	Ceiling

ADDITIONAL INFO

Warranty	5-Years

PACKAGING

UPC	045923683428
Case Cube	1.933
Case Height	12.13
Case Length	18.9
Case Quantity	4
Case UPC	10045923683425
Case Weight	21.12
Case Width	14.57
EA Cube	0.4156
EA Height	13.98
EA Length	11.34
EA Quantity	1
EA Weight	4.84
EA Width	4.53
Pack Type	Box
Web Height	4.88
Web Length	9.56
Web Width	9.56

COMPLIANCE

ADA Compliant	No
Bug Rating	B2-U3-G3
CA Prop 65	Lead
DLC ID	S-2G6G9R
FCC Compliant	Yes
IP Rating	IP65
Location Rating	Wet
NSF Approved	No
ROHS Compliant	Yes
Safety Listing	cULus
California Ban	Lawful for sale
DLC Approved	Yes
Title 20	Exempt
T24/JA8 Compliant	No

© Satco Products, Inc.
All rights reserved 2026