



Project / Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S11333 - 7.5 Watt; BR30 LED; 2700K; Medium base; 105 deg. Beam Angle; 120 Volt; 2-pack



GENERAL

Company	SATCO
EA Height	5.51
EA Width	3.86
EA Length	7.68
Candle Power	220.0
Center Beam Candle Power	220
Dimmable Text	Forward Phase or Reverse Phase or Phase Selectable
Lamp Filament	LED
Material	Metal / Plastic / Electronic Components
Fixture Type	Reflector
Status	Active
Style	Transitional
CCT Selectable	No
Wattage Selectable	No
Finish Family	Gray
Amps	0.063A
Has Camera	No
IOT Enabled	No
Lens Finish	Gray
Lens Material	Plastic (PS)
Lensed	Yes
Operating Position	Universal
Power Factor	0.92
SDS Class	LED_Lamp
Indoor Outdoor	Indoor
Product Technology	LED
Incandescent Equivalent	65W

PACKAGING

UPC	045923113338
Case Cube	1.3511
Case Height	12.01
Case Length	15.83
Case Quantity	12
Case UPC	10045923113335
Case Weight	7.67
Case Width	12.28
EA Cube	0.0945
EA Height	5.51
EA Length	7.68
EA Quantity	1
EA Weight	0.57
EA Width	3.86
Pack Type	Box
Web Length	5.157
Web Width	3.74

COMPLIANCE

FCC Compliant	Yes
Location Rating	Damp
ROHS Compliant	Yes
Safety Listing	cULus - Certified, cULus - Listed
California Ban	California T24 Listed
DLC Approved	No
Title 20	Yes
T24 Compliant	Yes

ELECTRICAL

CCT (Kelvin Temp)	2700K
Dimmable	Yes-Dimmable
Hours Rated	25000
Beam Angle (degree)	105
Color Temp	Warm White
CRI	90+
Dimming Type	120V only, Phase cut
Operating Frequency	60Hz
Operating Temp	-25C (-13F) to +45C (+113F)
Lumens	650L
Volts	120v
Watts	7.5W

PHYSICAL

Lamp Base	Medium
Finish	Gray
Housing Color	Gray
ANSI Base	E26
Lamp Type	BR30
MOD Lamps	3.74
MOL	5.157

ADDITIONAL INFO

Warranty	5-Years
Rated For Enclosed Fixture	Yes