



Project / Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S11444 - 14 Watt PAR38 LED; White; 5000K; 1100 Lumens; 120 Volt; PIR Sensor; Non-Dimmable



GENERAL

Company	SATCO
EA Height	5.91
EA Width	5.0
EA Length	5.0
Lamp Filament	LED
Material	Plastic
Fixture Type	PAR
Product Notes	Dual Mode Capable: Motion or On-Off Switch
Status	Active
Style	Utility
CCT Selectable	No
Wattage Selectable	No
Finish Family	White
Additional Info	The lamp has an integrated motion-activated sensor designed to activate between dusk and dawn. It remains inactive in the absence of motion but turns on for a duration of 5 minutes once motion is detected. This functionality can be overridden by toggling the bulb's switch on and off twice within a span of 3 seconds, allowing it to remain continuously illuminated like a standard light bulb.
Amps	0.117A
Has Camera	No
IOT Enabled	No
Operating Position	Universal
Photo Cell	Has PIR Sensor
Power Factor	0.8
SDS Class	LED_Lamp
Indoor Outdoor	Indoor, Outdoor
Product Technology	LED
Incandescent Equivalent	100W

PACKAGING

UPC	045923114441
Case Cube	1.4892
Case Height	14.17
Case Length	16.42
Case Quantity	12
Case UPC	10045923114448
Case Weight	11.51
Case Width	11.06
EA Cube	0.0855
EA Height	5.91
EA Length	5.0
EA Quantity	1
EA Weight	0.84
EA Width	5.0
Inner Cube	0.6156
Inner Height	6.5
Inner Length	15.63
Inner Quantity	6
Inner UPC	20045923114445
Inner Weight	5.03
Inner Width	10.47
Pack Type	Box
Web Length	5.35
Web Width	4.85

COMPLIANCE

FCC Compliant	Yes
Location Rating	Wet
ROHS Compliant	Yes
Safety Listing	cULus - Certified, cULus - Listed
California Ban	Lawful for sale
DLC Approved	No
Title 20	Yes
T24 Compliant	No

ELECTRICAL

CCT (Kelvin Temp)	5000K
Dimmable	Non-Dimmable
Hours Rated	15000
Beam Angle (degree)	40
Color Temp	Natural Light
CRI	90+
Operating Frequency	60Hz
Operating Temp	-4F to +104F (-20C to +40C)
Lumens	1150L
Volts	120v
Watts	14W

PHYSICAL

Lamp Base	Medium
Finish	WHITE
Housing Color	White
ANSI Base	E26
Lamp Type	PAR38
MOD Lamps	4.85
MOL	5.35

ADDITIONAL INFO

Warranty	2-Years
Installation Notes	To achieve optimal sensor reading, make sure the sensor is facing the desired motion area within proper distance and angle.
Rated For Enclosed Fixture	No