



Project / Job Name: \_\_\_\_\_

Location: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Notes: \_\_\_\_\_

**S11551** - 5.5 Watt LED PL 2-PIN Dual Mode; 3000K; 500 Lumens; GX23 base; 50000 Average rated hours; 120 deg. Beam Angle; Type A/B Ballast Dependent or Ballast Bypass; 120-277 Volt



**GENERAL**

Company	SATCO
EA Height	6.14
EA Width	0.94
EA Length	1.34
Lamp Ballast Type AB	Type A/B
Ballasting Requirements	Ballast required (Type A) or Ballast Bypass (Type B)
Lamp Filament	LED
Material	Glass / Plastic
Fixture Type	PL 2-Pin
Status	Discontinued
Style	Transitional
CCT Selectable	No
Wattage Selectable	No
Finish Family	White
Amps	0.046-0.020A
Has Camera	No
IOT Enabled	No
Lens Finish	Frost
Lens Material	Glass
Lensed	Yes
Operating Position	Universal
Power Factor	0.97
SDS Class	LED_Lamp
Indoor Outdoor	Indoor
Product Technology	LED
Fluor Equiv	13W
Incandescent Equivalent	45W

**ELECTRICAL**

CCT (Kelvin Temp)	3000K
Dimmable	Non-Dimmable
Hours Rated	50000
Beam Angle (degree)	120
Color Temp	Warm White
CRI	80+
Operating Frequency	50/60Hz
Operating Temp	-4F to +113F (-20C to +45C)
Lumens	500L
Volts	120V-277V
Watts	5.5W

**PHYSICAL**

Lamp Base	GX23
Finish	Frost
Housing Color	White
ANSI Base	GX23
Lamp Type	PL
MOD Lamps	1.26
MOL	5.98

**ADDITIONAL INFO**

Warranty	5-Years
Rated For Enclosed Fixture	No

**PACKAGING**

UPC	045923115516
Case Cube	0.3781
Case Height	7.09
Case Length	16.14
Case Quantity	50
Case UPC	10045923115513
Case Weight	7.72
Case Width	5.71
EA Cube	0.0045
EA Height	6.14
EA Length	1.34
EA Quantity	1
EA Weight	0.15
EA Width	0.94
Inner Cube	0.0624
Inner Height	6.61
Inner Length	5.31
Inner Quantity	10
Inner UPC	20045923115510
Inner Weight	1.54
Inner Width	3.07
Pack Type	Box
Web Length	5.98
Web Width	1.26

**COMPLIANCE**

FCC Compliant	Yes
Location Rating	Damp
ROHS Compliant	Yes
Safety Listing	cULus - Certified, cULus - Classified
California Ban	Lawful for sale
DLC Approved	No
Title 20	Exempt
T24/JA8 Compliant	No