SATCO | NUVO



Project / Job Name:

Location:

Fixture Type:

Notes:

**S11555** - 3.5 Watt; 2G7 Base; 27K/30K/35K/40K CCT Selectable; Frost Finish; Ballast Bypass; 120-277 Volt

DAMP LOCATION | cULus CLASSIFIED | FC | RoHS COMPLIANT | CCT SELECTABLE | 50,000 HOURS | TYPE B | 5 YEAR WARRANTY | 120-277V

## GENERAL

| | |
|---|---|
| Company | SATCO |
| EA Height | 4.84 |
| EA Width | 0.91 |
| EA Length | 1.54 |
| Lamp Ballast Type AB | Type B |
| Ballasting Requirements | Ballast Bypass |
| Lamp Filament | LED |
| Material | Polycarbonate (PC) |
| Fixture Type | PL |
| Status | Active |
| Style | Transitional |
| Surge Protection | Built-in-surge protection - 0.5KV |
| Total Harmonic Distortion | 20% |
| CCT Selectable | Yes |
| Wattage Selectable | No |
| Finish Family | White |
| Amps | 0.029-0.013A |
| Has Camera | No |
| IOT Enabled | No |
| Operating Position | Universal |
| Power Factor | 0.9 |
| SDS Class | LED_Lamp |
| Indoor Outdoor | Indoor |
| Product Technology | LED |
| Fluor Equiv | 5W/7W/9W |
| Serviceable Battery | No |
| Battery Indicator | No |
| Digital Display | No |

## ELECTRICAL

| | |
|---|---|
| CCT (Kelvin Temp) | 2700K/3000K/3500K/4000K |
| Dimmable | Non-Dimmable |
| Hours Rated | 50000 |
| Beam Angle (degree) | 120 |
| Color Temp | Warm to Cool White |
| CRI | 80+ |
| Operating Frequency | 50/60Hz |
| Operating Temp | -4F to +113F (-20C to +45C) |
| Lumens | 380L/390L/400L/410L |
| Volts | 120V-277V |
| Watts | 3.5W |
| Max Lumens | 410L |

## PHYSICAL

| | |
|---|---|
| Lamp Base | 2G7 (4-Pin) |
| Finish | Frost |
| Housing Color | White |
| ANSI Base | 2G7 |
| Lamp Type | PL |
| MOD Lamps | 1.26 |
| MOL | 4.74 |

## ADDITIONAL INFO

| | |
|---|---|
| Warranty | 5-Years |
| Rated For Enclosed Fixture | No |

## PACKAGING

| | |
|---|---|
| UPC | 045923115554 |
| Case Cube | 0.3441 |
| Case Height | 5.71 |
| Case Length | 18.11 |
| Case Quantity | 50 |
| Case UPC | 10045923115551 |
| Case Weight | 5.9 |
| Case Width | 5.75 |
| EA Cube | 0.0039 |
| EA Height | 4.84 |
| EA Length | 1.54 |
| EA Quantity | 1 |
| EA Weight | 0.08 |
| EA Width | 0.91 |
| Inner Cube | 0.0508 |
| Inner Height | 3.46 |
| Inner Length | 5.16 |
| Inner Quantity | 10 |
| Inner UPC | 20045923115558 |
| Inner Weight | 1.15 |
| Inner Width | 4.92 |
| Pack Type | Box |
| Web Length | 4.74 |
| Web Width | 1.26 |

## COMPLIANCE

| | |
|---|---|
| FCC Compliant | Yes |
| Location Rating | Damp |
| NSF Approved | No |
| ROHS Compliant | Yes |
| Safety Listing | cULus - Classified |
| California Ban | Lawful for sale |
| DLC Approved | No |
| Title 20 | Exempt |
| T24/JA8 Compliant | No |



© Satco Products, Inc.
All rights reserved 2026