SATCO | NUVO



Project / Job Name:

Location:

Fixture Type:

Notes:

S11580 - 5.5 Watt PAR20 LED; Medium Base; Silver Finish; CCT Selectable; 120 Volt; 25 Degree Beam Angle

WET LOCATION | 90+ CRI | DIMMABLE | ENCLOSED FIXTURE | cULus LISTED | FC | RoHS COMPLIANT | CCT SELECTABLE | 25,000 HOURS | 25° BEAM | 3 YEAR WARRANTY | 120 VOLT | TITLE 20 | TITLE 24

GENERAL

Company	SATCO
EA Height	3.5
EA Width	2.64
EA Length	2.64
Center Beam Candle Power	1255
Lamp Filament	LED
Material	Polyamide (PA)
Fixture Type	PAR
Spot Type	SP - Spot
Status	Active
Style	Utility
CCT Selectable	Yes
Wattage Selectable	No
Finish Family	Silver
Amps	0.078A
Has Camera	No
IOT Enabled	No
Lens Finish	Clear
Lens Material	Polycarbonate (PC)
Lensed	Yes
Operating Position	Universal
Power Factor	0.7
SDS Class	LED_Lamp
Indoor Outdoor	Indoor, Outdoor
Product Technology	LED
Fluor Equiv	11W
Incandescent Equivalent	50W
Serviceable Battery	No
Battery Indicator	No
Digital Display	No

ELECTRICAL

CCT (Kelvin Temp)	2700K/3000K/3500K/4000K/5000K
Dimmable	Yes-Dimmable
Hours Rated	25000
Beam Angle (degree)	25
Color Temp	Warm White to Natural Light
CRI	90+
Dimming Type	120V only, Phase Cut (TRIAC)
Operating Frequency	60Hz
Operating Temp	-4F to +104F (-20C to +40C)
Lumens	500L
Volts	120v
Watts	5.5W

PHYSICAL

Lamp Base	Medium
Finish	SILVER
Housing Color	Silver
ANSI Base	E26
Lamp Type	PAR20
MOD Lamps	2.48
MOL	3.19

ADDITIONAL INFO

Warranty	3-Years
Rated For Enclosed Fixture	Yes

PACKAGING

UPC	045923115806
Case Cube	0.5747
Case Height	17.52
Case Length	4.72
Case Quantity	24
Case UPC	10045923115803
Case Weight	5.34
Case Width	12.01
EA Cube	0.0141
EA Height	3.5
EA Length	2.64
EA Quantity	1
EA Weight	0.17
EA Width	2.64
Inner Cube	0.1101
Inner Height	8.46
Inner Length	3.94
Inner Quantity	6
Inner UPC	20045923115800
Inner Weight	1.16
Inner Width	5.71
Pack Type	Box
Web Length	3.19
Web Width	2.48

COMPLIANCE

FCC Compliant	Yes
Location Rating	Wet
ROHS Compliant	Yes
Safety Listing	cULus - Certified, cULus - Listed
California Ban	Lawful for sale
DLC Approved	No
Title 20	Yes
T24/JA8 Compliant	Yes

© Satco Products, Inc.
All rights reserved 2026