Project / Job Name:

Location:

Fixture Type:

Notes:



S11614 - 12 watt LED Direct Wire Downlight; Edge-lit; 6 inch; 5000K; 120 volt; Dimmable; Square; Remote Driver

GENERAL

Company	SATCO
EA Height	7.13
EA Width	2.13
EA Length	8.74
Bulb Included	Integrated
Material	Aluminum
Fixture Type	Remote Driver LED Downlight
Status	Discontinued
CCT Selectable	No
Wattage Selectable	No
Finish Family	White
Additional Info	Integrated j-box for direct wire installation
Amps	0.100A
Has Camera	No
IOT Enabled	No
Lens Finish	Frost
Lens Material	Poly methyl methacrylate (PMMA)
Power Factor	0.99
SDS Class	LED_Lamp
Sloped Ceiling Compatible	No
Indoor Outdoor	Indoor
Product Technology	LED
Incandescent Equivalent	75W
Serviceable Battery	No
Battery Indicator	No
Digital Display	No

ELECTRICAL

CCT (Kelvin Temp)	5000K
Dimmable	Yes-Dimmable
Hours Rated	50000
Beam Angle (degree)	108
Color Temp	Natural Light
CRI	90+
Dimming Type	120V only, Phase Cut (TRIAC)
Operating Temp	-4F to +113F (-20C to +45C)
Lumens	820L
Volts	120v
Watts	12W
Connection	Direct Wired

PHYSICAL

Lamp Base	Integrated
Finish	WHITE
ANSI Base	Integrated
Lamp Type	Integrated LED
Fixture Shape	Square
Mounting Procedure	Ceiling

ADDITIONAL INFO

Warranty	5-Years
Installation Notes	**If you purchase The 5W Emergency Driver (S8000) or the 10W Emergency Driver (S8002), you must also purchase the Emergency Driver Enclosure (80-973)

PACKAGING

UPC	045923116148
Case Cube	1.1306
Case Height	15.24
Case Length	13.74
Case Quantity	12
Case UPC	10045923116145
Case Weight	18.63
Case Width	9.33
EA Cube	0.0768
EA Height	7.13
EA Length	8.74
EA Quantity	1
EA Weight	1.3
EA Width	2.13
Pack Type	Box
Web Height	0.94
Web Length	6.75
Web Width	6.75

COMPLIANCE

Air Tight	Yes
CA Prop 65	Lead
FCC Compliant	Yes
IC Rated	Yes
Location Rating	Wet
ROHS Compliant	Yes
Safety Listing	cETLus - Listed
California Ban	Lawful for sale
UL Application	Ceiling
DLC Approved	No
Energy Star Certified	No
Title 20	Exempt
T24/JA8 Compliant	No

© Satco Products, Inc.
All rights reserved 2026