



Project / Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S11623 - 12 watt LED Direct Wire Downlight; Gimbale; 4 inch; 3000K; 120 volt; Dimmable; Square; Remote Driver; Brushed Nickel



GENERAL

| | |
|---------------------------|---|
| Company | SATCO |
| EA Height | 5.39 |
| EA Width | 3.54 |
| EA Length | 7.24 |
| Bulb Included | Integrated |
| Material | Aluminum |
| Fixture Type | Remote Driver LED Downlight |
| Product Notes | Aiming Angle: 30dg |
| Status | Discontinued |
| Style | Utility |
| CCT Selectable | No |
| Wattage Selectable | No |
| Finish Family | Nickel |
| Additional Info | Integrated j-box for direct wire installation |
| Amps | 0.100A |
| Has Camera | No |
| IOT Enabled | No |
| Lens Finish | Clear |
| Lens Material | Polycarbonate (PC) |
| Power Factor | >0.9 |
| SDS Class | LED_Lamp |
| Sloped Ceiling Compatible | Yes |
| Indoor Outdoor | Indoor |
| Product Technology | LED |
| Incandescent Equivalent | 75W |

ELECTRICAL

| | |
|---------------------|-----------------------------|
| CCT (Kelvin Temp) | 3000K |
| Dimmable | Yes-Dimmable |
| Hours Rated | 50000 |
| Beam Angle (degree) | 40 |
| Color Temp | Warm White |
| CRI | 90+ |
| Dimming Type | 120V only, Phase cut |
| Operating Frequency | 60Hz |
| Operating Temp | -4F to +113F (-20C to +45C) |
| Lumens | 850L |
| Volts | 120v |
| Watts | 12W |

PHYSICAL

| | |
|---------------|----------------|
| Lamp Base | Integrated |
| Finish | Brushed Nickel |
| ANSI Base | Integrated |
| Lamp Type | Integrated LED |
| Fixture Shape | Square |

ADDITIONAL INFO

| | |
|--------------------|---|
| Warranty | 5-Years |
| Installation Notes | **If you purchase The 5W Emergency Driver (S8000) or the 10W Emergency Driver (S8002), you must also purchase the Emergency Driver Enclosure (80-973) |

PACKAGING

| | |
|---------------|----------------|
| UPC | 045923116230 |
| Case Cube | 1.1861 |
| Case Height | 11.77 |
| Case Length | 22.24 |
| Case Quantity | 12 |
| Case UPC | 10045923116237 |
| Case Weight | 21.62 |
| Case Width | 7.83 |
| EA Cube | 0.0799 |
| EA Height | 5.39 |
| EA Length | 7.24 |
| EA Quantity | 1 |
| EA Weight | 1.55 |
| EA Width | 3.54 |
| Pack Type | Box |
| Web Height | 2.0 |
| Web Length | 4.88 |
| Web Width | 4.88 |

COMPLIANCE

| | |
|-----------------------|-----------------------|
| Air Tight | Yes |
| CA Prop 65 | Lead |
| FCC Compliant | Yes |
| IC Rated | Yes |
| Location Rating | Wet |
| ROHS Compliant | Yes |
| Safety Listing | cETLus - Listed |
| California Ban | California T24 Listed |
| UL Application | Ceiling |
| DLC Approved | No |
| Energy Star Certified | No |
| Title 20 | Exempt |
| T24/JA8 Compliant | Yes |