SATCO | NUVO

Project / Job Name:

Location:

Fixture Type:

Notes:



**S11629** - 12 watt LED Direct Wire Downlight; Gimbaled; 3.5 inch; 3000K; 120 volt; Dimmable; Square; Remote Driver; Brushed Nickel

WET LOCATION | 90+ CRI | DIMMABLE | ETL | FC | RoHS | 50,000 HOURS | 40° BEAM | AIR TIGHT | 5 YEAR WARRANTY | 120 VOLT | IC RATED | TITLE 24

## GENERAL

| | |
|---|---|
| Company | SATCO |
| EA Height | 4.8 |
| EA Width | 4.88 |
| EA Length | 6.06 |
| Bulb Included | Integrated |
| Material | Aluminum |
| Fixture Type | Remote Driver LED Downlight |
| Product Notes | Aiming Angle: 15dg |
| Status | Discontinued |
| Style | Utility |
| CCT Selectable | No |
| Wattage Selectable | No |
| Finish Family | Nickel |
| Additional Info | Integrated j-box for direct wire installation |
| Amps | 0.100A |
| Has Camera | No |
| IOT Enabled | No |
| Lens Finish | Clear |
| Lens Material | Polycarbonate (PC) and Glass |
| Power Factor | >0.9 |
| SDS Class | LED_Lamp |
| Sloped Ceiling Compatible | Yes |
| Indoor Outdoor | Indoor |
| Product Technology | LED |
| Incandescent Equivalent | 75W |
| Serviceable Battery | No |
| Battery Indicator | No |
| Digital Display | No |

## ELECTRICAL

| | |
|---|---|
| CCT (Kelvin Temp) | 3000K |
| Dimmable | Yes-Dimmable |
| Hours Rated | 50000 |
| Beam Angle (degree) | 40 |
| Color Temp | Warm White |
| CRI | 90+ |
| Dimming Type | 120V only, Phase Cut (TRIAC) |
| Operating Frequency | 60Hz |
| Operating Temp | -4F to +113F (-20C to +45C) |
| Lumens | 840L |
| Volts | 120v |
| Watts | 12W |
| Connection | Direct Wired |

## PHYSICAL

| | |
|---|---|
| Lamp Base | Integrated |
| Finish | Brushed Nickel |
| ANSI Base | Integrated |
| Lamp Type | Integrated LED |
| Fixture Shape | Square |
| Mounting Procedure | Ceiling |

## ADDITIONAL INFO

| | |
|---|---|
| Warranty | 5-Years |
| Installation Notes | **If you purchase The 5W Emergency Driver (S8000) or the 10W Emergency Driver (S8002), you must also purchase the Emergency Driver Enclosure (80-973) |

## PACKAGING

| | |
|---|---|
| UPC | 045923116292 |
| Case Cube | 1.223 |
| Case Height | 10.63 |
| Case Length | 15.63 |
| Case Quantity | 12 |
| Case UPC | 10045923116299 |
| Case Weight | 20.46 |
| Case Width | 12.72 |
| EA Cube | 0.0821 |
| EA Height | 4.8 |
| EA Length | 6.06 |
| EA Quantity | 1 |
| EA Weight | 1.46 |
| EA Width | 4.88 |
| Pack Type | Box |
| Web Height | 3.0 |
| Web Length | 4.38 |
| Web Width | 4.38 |

## COMPLIANCE

| | |
|---|---|
| Air Tight | Yes |
| CA Prop 65 | Lead |
| FCC Compliant | Yes |
| IC Rated | Yes |
| Location Rating | Wet |
| ROHS Compliant | Yes |
| Safety Listing | cETLus - Listed |
| California Ban | California T24 Listed |
| UL Application | Ceiling |
| DLC Approved | No |
| Energy Star Certified | No |
| Title 20 | Exempt |
| T24/JA8 Compliant | Yes |



© Satco Products, Inc.
All rights reserved 2026